



Rid-Ox™

Connector Protector/Enhancer

2112

Introduction

A protective coating containing polyphenyl ether, which provides a micro thin shield against oxidation. Rid-Ox™ is designed to protect electronic connections during storage, transportation and operation. Rid-Ox™ is a premium product designed specifically for improving conductivity, while sealing and protecting connectors and contacts. It is formulated as a contact enhancer/ preservative and is ideal for lubricating and protecting surfaces from further oxidation.

Features / Benefits

- Improves Conductivity
- Prevents Oxidation
- Seals & Protects
- Reduces Connection Failures
- Reduces Wear & Abrasion

Chemical Components

Aliphatic Hydrocarbon Mixture.....	(64742-47-8)	
	(64742-53-6)	75-82%
Proprietary Protectant		<1%
Barium Dinonylnaphthalene Sulfonate.....	(25619-56-1)	<<1%
1,1,1,2-Tetrafluoroethane.....	(811-97-2)	17-21%

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Rid-Ox™ is available in the following sizes:

- 2112-6S 6 Ounce Aerosol

MATERIAL SAFETY DATA SHEET

Finished Product



MSDS Ref. No: 2112-6S

Rid Ox

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Rid Ox

PRODUCT DESCRIPTION: Connector Protector Enhancer

PRODUCT CODE: 2112/CAN/EUR-6S

MANUFACTURER

Techspray, L.P.

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
Distillates, petroleum, hydrotreated light	60 - 80	64742-47-8	265-149-8
1,1,1,2-Tetrafluoroethane (HFC-134a)	15 - 25	811-97-2	223770
Nitromethane	<1	75-52-5	

EEC LABEL SYMBOL AND CLASSIFICATION



R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.

EEC Harmful - "Xn"

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Flammable liquid and vapor.

POTENTIAL HEALTH EFFECTS

EYES: Substance causes substantial eye irritation.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Harmful if swallowed.

INHALATION: High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Symptoms of overexposure include: stinging, tearing, redness and pain.

INGESTION: For large amounts; abdominal pain, nausea and vomiting.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Aspiration hazard. If swallowed, vomiting may occur spontaneously, but do not induce. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Call a physician immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: 44°C (111°F)TAG CC

FLAMMABLE LIMITS: 1.4 to 9.3

GENERAL HAZARD: Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

EXPLOSION HAZARDS: Vapors may form explosive mixture with air.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Pink/red.

pH: Not Applicable

PERCENT VOLATILE: 96 at 20°C (68°F)

BOILING POINT: 149°C (300°F)

SOLUBILITY IN WATER: Insoluble

SPECIFIC GRAVITY: 0.79 (water=1)

VISCOSITY: Not Applicable

(VOC): 786 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

STABLE: YES

HAZARDOUS POLYMERIZATION: NO

CONDITIONS TO AVOID: Heat, flames, ignition sources, and incompatibles.

STABILITY: Stable.

INCOMPATIBLE MATERIALS: Concentrated nitric and sulfuric acid mixtures, chloroform, alkalis, chlorine compounds, acids, potassium t-butoxide.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Not Available

SKIN EFFECTS: Not Available

CARCINOGENICITY:

IARC: NOT listed

NTP: NOT listed

OSHA: NOT listed

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

13. DISPOSAL CONSIDERATIONS

GENERAL COMMENTS: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

PRIMARY HAZARD CLASS/DIVISION: No classification

UN/NA NUMBER: NA

PACKING GROUP: NA

AIR (ICAO/IATA)

PROPER SHIPPING NAME: CONSUMER COMMODITY ID8000

PRIMARY HAZARD CLASS/DIVISION: 9

UN/NA NUMBER: ID8000

PACKING GROUP: NA

IATA NOTE: Domestic shipments only. When shipping International contact TechSpray shipping department.

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: AEROSOLS IN LIMITED QUANTITIES OF CLASS 2

PRIMARY HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN1950

PACKING GROUP: NA

IMDG NOTE: Page 2102

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES:

FIRE: YES **PRESSURE GENERATING:** NO **REACTIVITY:** NO **ACUTE:** YES
CHRONIC: YES

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None of the ingredients are CERCLA/Superfund hazardous chemicals.

CERCLA RQ: 1000 Lbs.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are either listed or exempt from listing in the TSCA inventory.

OSHA HAZARD COMM. RULE: Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.