



# Flux Remover Pen

Trace Technologies™  
2506

## Introduction

---

The Flux Remover Pen provides a convenient method for touch-up cleaning of flux residues. This pen is a unique combination of hydrocarbon solvents and alcohols making it an excellent defluxer. Safe on plastics and rapid evaporating, the Flux Remover Pen dissolves type R, RMA, SA and most no-clean fluxes. Can also be used as an all-purpose cleaner for removal of light oils, silicones, waxes, greases and similar contaminants.

### Features / Benefits

- Complete Removal of Flux Instantly
- Pen Tip Allows Controlled Application
- Fast Drying

## Chemical Components

---

Isopropanol.....	(67-63-0)	80-85%
Hexane Isomers Consisting of:		
n-Hexane.....	(110-54-3)	5-7%
Methycyclo Pentane.....	(96-37-7)	1-2%
Methyl Pentane.....	varies	2-3%

## Environmental Policy

---

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

## Packaging and Availability

---

Flux Remover Pen is available in the following sizes:

- 2506-N                      1 11.5ml Pen

## Resources

---

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email [tsales@techspray.com](mailto:tsales@techspray.com) or visit our web site at: [www.techspray.com](http://www.techspray.com).

**North America**

Tech Spray L.P.  
P.O. Box 949  
Amarillo, TX 79105  
800-858-4043  
email: [tsales@techspray.com](mailto:tsales@techspray.com)

**Europe**

Techspray International  
UNIT 4, 44/46 Bunyan Road, Kempston  
Bedford MK42 8HL United Kingdom  
+44 (0) 1234 855443  
email: [tseurope@techspray.com](mailto:tseurope@techspray.com)

**Countries Outside US**

Call to locate a distributor  
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.  
P.O. Box 949  
Amarillo, TX 79105  
[www.techspray.com](http://www.techspray.com)

[English MSDS](#)  
[French MSDS](#)  
[German MSDS](#)  
[Italian MSDS](#)  
[Spanish MSDS](#)



Copyright 2003 Tech Spray, L. P.

**For Commercial Use Only**