

Material Safety Data Sheet

Revision Date February 4 th , 2005	Prepared by David MacKinnon	Technical Information 1-800-201-8822 or support@mgchemicals.com
Head Office 9347 - 193 Street, Surrey, B.C., V4N 4E7		Emergency Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 835 - liquid

Name: Rosin Flux

Related Part Numbers: 835-100ML; 835-1L; 835-4L

Use: Soldering flux for electrical and electronic applications.

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
8050-09-7	rosin	40 - 60	n/e	n/e	n/e
78-92-2	2-butanol	20 - 30	150ppm	100ppm	n/e
64-17-5	ethanol	20 - 30	1000ppm	1000ppm	1000ppm

Section 3: Hazards Identification

WHMIS Codes: B2, D2B

NFPA Ratings: Health 1 Flammability 3 Reactivity 0

HMIS Ratings: Health 1 Flammability 3 Reactivity 0

Eyes: Liquid and smoke from soldering can cause eye irritation.

Skin: May cause skin irritation.

Inhalation: Fumes during soldering may irritate mucous membranes and respiratory system. High concentrations can cause headache, dizziness, narcosis and nausea.

Ingestion: May cause burning sensation in the digestive tract.

Chronic: Prolonged or repeated skin contact can result in a rash.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid.

Skin: Wash skin with large amounts of soap and water. Get medical aid if symptoms persist.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

Section 5: Fire Fighting Measures

Autoignition Temperature: 382°C **Flash Point:** 18°C **LEL / UEL:** 2.5 / 15

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Information: Will burn if involved in a fire.

Section 6: Accidental Release Measures

Spill Procedure: Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection. Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well ventilated area, away from incompatible substances.

Section 8: Exposure Controls

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

Personal Protection: Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

Section 9: Physical and Chemical Properties

Physical State:	liquid	Odor:	alcohol	Solubility:	50% in water	Evaporation Rate:	1.9 (ether=1)		
Boiling Point:	76°C	Specific Gravity:	0.93	Vapor Pressure:	1 PSI @21°C	Vapor Density:	1.8 (Air=1)	pH:	n/a

Section 10: Stability and Reactivity

Stability:	Stable at normal temperatures and pressures.
Conditions to avoid:	Temperatures over 40°C, ignition sources, and incompatible materials. Exposure to moist air or water.
Incompatibilities:	Strong oxidizers
Polymerization:	Will not occur.
Decomposition:	Aliphatic aldehydes, acids, terpenes, carbon dioxide, carbon monoxide.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure)	Not known to.
Carcinogenicity: (risk of cancer)	Not known to.
Teratogenicity: (risk of malformation in an unborn fetus)	Not known to.
Reproductive Toxicity: (risk of sterility)	Not known to.
Mutagenicity: (risk of heritable genetic effects)	Not known to.
Lethal Exposure Concentrations:	Ingestion(LD50): 6.5 g/kg Inhalation (LC50): 20 g/kg Skin (LD50): n/e

Section 12: Ecological Information

General Information: Avoid runoff into storms and sewers which lead into waterways. Water runoff can cause environmental damage.

Environmental Impact Data: (percentage by weight)

CFC: 0 **HFC:** 0 **Cl.Solv.:** 0 **VOC:** 50 **HCFC:** 0 **ODP:** 0

Section 13: Disposal Information

General Information: Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff can cause environmental damage.

Section 14: Transportation Information

Ground:(all sizes 1 litre or less)

Consumer Commodity, ORM-D

Ground: (all sizes larger than 1 litre)

Shipping name—Alcohol N.O.S (Ethanol), Class III, UN#1987, Packing Group II. Shipper must be trained and certified. Refer to CFR 49, TDG regulations (Canada).

Air:

Shipper must be trained and certified. Refer to IATA regulations.

Sea

Shipper must be trained and certified. Refer to IMDG regulations.

Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depletors.

This product does not contain any class 2 ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, May 1, 1997 revision, USA)

This product does not contain any chemicals listed.

Health Canada:

Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations.

Environment Canada:

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act

This product does not contain any ozone depleting substances.

Industry and Science Canada:

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

RoHS (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

Section 16: Other Information

Definitions: n/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of



Registered Quality System **ISO 9001**
QMI Certificate #004008
Toronto, Ontario, Canada

the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.