

This document was generated on 05/18/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0194021000 Status: Active

**Description:** Self-Contained Tap Splice Connector for Solid Nonmetallic Sheathed Cable, 12-14

**Documents:** 

3D Model Product Specification PS-19902-011 (PDF) Drawing (PDF) RoHS Certificate of Compliance (PDF)

**Agency Certification** 

CSA LR18689 UL E182087

General

Product Family I/O Connectors Series 19402 Wire-to-Wire Application Component Type Plug, Receptacle MolexKits Yes Product Literature Order No 987650-0531

**Product Name** SCPC Type N/A

**Physical** 

Circuits (Loaded) 2 Circuits (maximum) 2

Circuits Detail 2 Circuits with Ground

Color - Resin Clear, Natural Durability (mating cycles max) 250

94-5VA Flammability Lock to Mating Part Yes Material - Metal High Copper

Material - Plating Mating Material - Plating Termination

Material - Resin Polycarbonate, Polyester

Number of Rows Orientation Right Angle PCB Retention N/A Packaging Type Bag

Panel Mount Nο Pitch - Mating Interface 10.10mm (.398") 1.016µm (40µ") Plating min - Mating Plating min - Termination 1.016µm (40µ")

Polarized to Mating Part Yes Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -35°C to +85°C Termination Interface: Style **IDT** or Pierce 12, 14

Wire Size AWG


**Electrical** 

Current - Maximum per Contact 20A Voltage - Maximum 300V

**Material Info** 

Old Part Number COC-3

**Reference - Drawing Numbers** 



**EU RoHS ELV and RoHS** Compliant **REACH SVHC** Not Reviewed Low-Halogen Status Not Reviewed

## **China RoHS**

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series

19402Series

**Mates With** 

19045-1000 Self-Contained Power Connector for Solid Cable, 12 to 14 AWG, 19403-1310 Self-Contained Splice Connector, Waterproof Version, 12 to 16 AWG, 19403-0011 Self-Contained Power Connector for Stranded Cable, 14 AWG, 19421-0001 Self-Co

**Use With** 

19045-3180 Safety Cap

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product # Hand Crimp Tool 0192850074 Hand Crimp Tool, SC0640015300

**Power Connectors** 

This document was generated on 05/18/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION