

No-Clean Desoldering Braid 1814-1825

Desoldering braid (wick) is pre-fluxed copper braid that is used to remove solder, which allows components to be replaced and excess solder to be removed.

Techspray wick is available in static dissipative bobbins (except where indicated) for static sensitive environments.





No-clean flux coated braid -- cleanest in the industry!

Techspray NoClean wick does not leave behind ionic flux residues that can collect and form branches called "dendrites". Other fluxes, if not cleaned properly, can cause dendrites that grow over time (see A, B) and eventually cause short circuits between traces or leads (C). Latent failures lead to costly returns and lower the quality perception of your products.

- No-clean flux coated braid
- · Cleanest wick -- clear, non-reactive residues
- Will not leave ionic residue -- avoid dendrite failure
- Exceeds MIL-F-14256, Type
- · Anti-static spool (except where indicated)

Product Packaging

1814-100F No-Clean White #1 Braid 100' 1 units/case



1816-5F No-Clean Green #3 Braid 5' 25 units/case




1815-5F No-Clean Yellow #2 Braid 5' 25 units/case



1816-10F No-Clean Green #3 Braid 10' 25 units/case



1815-10F No-Clean Yellow #2 Braid 10' 25 units/case



1816-50F No-Clean Green #3 Braid 50' 1 units/case





1817-5F No-Clean Blue #4 Braid 5' 25 units/case



1820-10F No-Clean White #1 Braid - AS 10' 25 units/case



No-Clean Yellow #2 Braid - AS 50' 1 units/case



1823-5F No-Clean Blue #4 Braid - AS 5' 25 units/case

1817-10F No-Clean Blue #4 Braid 10' 25 units/case



1820-50F No-Clean White #1 Braid - AS 50' 1 units/case



1822-5F No-Clean Green #3 Braid - AS 5' 25 units/case



1823-10F No-Clean Blue #4 Braid - AS 10' 25 units/case

1817-100F No-Clean Blue #4 Braid 100' 1 units/case



1821-5F No-Clean Yellow #2 Braid - AS 5' 25 units/case



1822-10F No-Clean Green #3 Braid - AS 10' 25 units/case



1823-25F No-Clean Blue #4 Braid - AS 25' 1 units/case









1825-5F No-Clean Red #6 Braid - AS 25 units/case





Chemical & Physical Properties			
Appearance			
Odor			
Flash Point			
VOC (EPA)			
VOC (CARB)			
Boiling Point			
Density			

Chemical Composition

CHEMICAL NAME	CAS#	
Non-ionic flux mixture (Proprietary non-hazardous blend)	7440-50-8	
Copper		

Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources





Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray P.O. Box 949 Amarillo, TX 79105 800-858-4043

email: tsales@techspray.com

Europe

Saffierlaan 5
2132 VZ Hoofddorp
The Netherlands
+31 88 1307 400
email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

