

## This document was generated on 06/07/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Description of				
Part Number:	<u>0015060100</u>			
Status:	Active			
Overview:	<u>minifit_bmi</u>			
Description:	4.20mm (.165") Pitch Min	i-Fit BMI™ Receptacle Housing, Dual Row with Panel Mount		
	Ears, PA Polyamide Nylo	n 6/6, UL 94V-2, 10 Circuits		
Documents:				
<u>3D Model</u>		Product Specification PS-5556-002 (PDF)		
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Series	
A momour Contified	ation		image - Reference only	
Agency Certifica	ation	1 010000		
CSA TUV		LR19980 R72081037	EU RoHS China RoHS	
UL		E29179	ELV and RoHS	
02		220110	Compliant	
General			REACH SVHC	
Product Family		Crimp Housings	Contains SVHC: No	
Series		<u>42474</u>	Halogen-Free	
Comments		Current = 13A max. per circuit when header is mated	Status	
		to a receptacle loaded with $\frac{45750}{2}$ series terminals	Halogen-Free	
		crimped to 16 AWG wire See Molex product specification PS-45750-001 for additional current de-	Need more information on product	
		rating information.	environmental compliance?	
MolexKits		Yes	Email productcompliance@molex.com	
Overview		minifit_bmi	For a multiple part number RoHS Certificate of	
Product Name		Mini-Fit BMI™	Compliance, <u>click here</u>	
<b>.</b>			Please visit the Contact Us section for any	
Physical			non-product compliance questions.	
Breakaway		No		
Circuits (maximum) Color - Resin		10 Natural		
Flammability		94V-2		
Gender		Female	Search Parts in this Series	
Glow-Wire Complian	t	No	<u>42474</u> Series	
Lock to Mating Part		None		
Material - Resin		Nylon	Mates With	
Number of Rows		2	<u>42475</u> Mini-Fit BMI™ Plug Housing. <u>43879</u>	
Packaging Type		Bag	MiniFit CPI™ Header. Mini-Fit BMI™	
Panel Mount	voo (in)	Yes	Header <u>42404</u> , <u>42440.</u> Mini-Fit SMC <sup>™</sup>	
Pitch - Mating Interfa Pitch - Mating Interfa		0.165 ln 4.20 mm	Surface Mount Compatible Header <u>43810</u> , 44068	
Polarized to Mating F		Yes		
Stackable		No	Use With	
Temperature Range	- Operating	-40°C to +105°C	<u>5556</u> Mini-Fit™ Crimp Terminal	
Electrical				
Electrical	or Contact	124		
Current - Maximum p		13A		
Material Info				
Old Part Number		42474-1011		
Boforonco Dro	wing Numbers			
Reference - Dray		DK 43474 004		
Packaging Specificat Product Specification		PK-42474-001 PS-5556-002		
Sales Drawing	1	SD-42474-****		
Test Summary		TS-5556-002		
		. 5 5000 002		

This document was generated on 06/07/2010
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION