


NLC-MOD-RTC

Order No.: 2701153




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2701153>

Real-time clock

Commercial data	
GTIN (EAN)	
sales group	K253
Pack	1 pcs.
Customs tariff	91109000
Catalog page information	Page 17 (AX-2011)

Product notes

WEEE/RoHS-compliant since:
04/18/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Interfaces	
Interface	Realtime Clock
Connection method	Slot 2

Supply	
Supply voltage	24 V DC (Power available via base unit)
Max. current consumption	10 mA

Typical current consumption	4 mA
-----------------------------	------

Realtime clock

Realtime clock	Yes (battery-backed)
Accuracy realtime clock	2 s/day at 25 °C
	4.5 s/day overall (60°C)
Battery	Life 5 years

General data

Width	24.5 mm
Height	25.5 mm
Depth	49 mm
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	90 %

Accessories

Item	Designation	Description
------	-------------	-------------

General

2701292	NLC-MOD-CAP-PXC	Replacement cover for slot 2 in base unit.
---------	-----------------	--

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;