


PSI-MODEM-GSM/ETH

Order No.: 2313355




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2313355>

Industrial GSM modem with GPRS/EDGE for mounting on EN DIN rail. GSM and GPRS/EDGE. 850 + 900 + 1800 + 1900 MHz. Ethernet interface. Firewall and VPN support. 6 alarm inputs and 4 switching outputs. Supply voltage 24 V DC.

Commercial data	
GTIN (EAN)	
sales group	H661
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 543 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
08/04/2008



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Serial interface	
Interface 1	Ethernet interface, 10/100BASE-T(X) in acc. with IEEE 802.3u
Transmission length	100 m (shielded twisted pair)
Connection method	RJ45 female connector, shielded
Serial transmission speed	10/100 Mbps, autonegotiation

Power supply

Nominal supply voltage	24 V DC \pm 5% (as an alternative or redundant, via backplane bus contact and system current supply)
Supply voltage range	10 V DC ... 30 V DC (via pluggable COMBICON screw terminal block)
Typical current consumption	< 360 mA (24 V DC)
	< 90 mA

General data

Width	35 mm
Height	99 mm
Depth	114.5 mm
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Ambient temperature (operation)	-25 °C ... 60 °C
Electrical isolation	(VCC // GSM // Ethernet // PE)
Test voltage data interfaces	1.5 kV
Test voltage data interface/data interface	1.5 kV (50 Hz, 1 min.)
Test voltage data interface/power supply	1.5 kV
	1.5 kV (50 Hz, 1 min.)
Electromagnetic compatibility	Conformance with R&TTE directive 1999/5/EC
Noise immunity	EN 61000-6-2:2005
Degree of protection	IP20
Net weight	300 g
Housing material	PA 6.6-FR
Color	green
UL, USA / Canada	cULus listed UL 508

Radio interface

Interface description	GSM / GPRS / EDGE
Frequency	850 MHz (2 W (EGSM))
	900 MHz (2 W (EGSM))
	1800 MHz (1 W (EGSM))
	1900 MHz (1 W (EGSM))
Antenna	50 Ω impedance SMA antenna socket
SIM interface 1	1.8 volt, 3 volt
GPRS	Class 12, Class B
	CS1 ... CS4

EDGE	Multislot Class 10
Network function	4 time slots for receiving data, 4 time slots for transmitting data. The PIN is saved in the modem. After a voltage interruption, there is automatic redialing into the network. Integrated TCP/IP stack, firewall and VPN support, independent connection establishment.
Network check	LED to show data signal quality

Certificates / Approvals



Certification CUL Listed, UL Listed

Accessories

Item	Designation	Description
Antennas		
2900982	PSI-GSM/UMTS-ANT-OMNI-2-5	GSM/UMTS omnidirectional antenna, 2 dBi gain, 5 m antenna cable with SMA circular connector
2313371	PSI-GSM/UMTS-QB-ANT	GSM UMTS antenna, with omnidirectional characteristic, 2 m antenna cable with SMA round connector
Cable/conductor		
2900980	PSI-CAB-GSM/UMTS- 5M	GSM/UMTS antenna cable, 5 m long; SMA (male) -> SMA (female), 50 Ohm impedance
2900981	PSI-CAB-GSM/UMTS-10M	GSM/UMTS antenna cable, 10 m long; SMA (male) -> SMA (female), 50 Ohm impedance
General		
2800491	CSMA-LAMBDA/4-2.0-BS-SET	Attachment plug with Lambda/4 technology as surge protection for coaxial signal interfaces. Connection: Male/female SMA connectors.
2709561	ME 17,5 TBUS 1,5/ 5-ST-3,81 GN	DIN rail connector for DIN rail power supply unit, gold-plated contacts, for DIN rail mounting, 5-pos.
2866983	MINI-SYS-PS-100-240AC/24DC/1.5	DIN rail power supply unit, primary-switched mode, slim design, output: 24 V DC / 1.5 A

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;