


GSTB 3/ 3-ST-7,62

Order No.: 1750171

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1750171>Plug component, Nominal current: 20 A, Number of positions: 3, Pitch:
7.62 mm, Connection method: Screw connection, Color: green**Commercial data**

GTIN (EAN)	 4 017918 028275
Note	Made-to-order
sales group	E072
Pack	50 pcs.
Customs tariff	85369010

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Certification

UL

Accessories

Item	Designation	Description
General		
1750142	CS-STB	Coding profile, for plugging into the coding ribs of the plug at a later date, insulating material, color: Red
Marking		
1051993	B-STIFT	Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm
1401844	BN-ZB 7,5/WH:UNBEDRUCKT	BN Zack strip, unprinted: 10-section, for individual labeling with M-PEN or CMS system, sufficient for labeling 100 terminal blocks
1400052	BNB-ZB 7,5,LGS:FORTL.ZAHLEN	BNB Zack strip, printed horizontally: 10-section, divisible, with consecutive numbers, 1-10, 11-20 etc. up to 991-1000
Plug/Adapter		
0201731	MPS-IH BK	Insulating sleeve, Color: black
0201702	MPS-IH GN	Insulating sleeve, Color: green
0201676	MPS-IH RD	Insulating sleeve, Color: red
0201663	MPS-IH WH	Insulating sleeve, Color: white
0201744	MPS-MT	Test plugs
0201647	RPS	Reducing plug, Color: gray

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;