

# UM-16 RELS/KSR-G24/ 1/N/PE/PLC

## Discontinued item


Order No.: 2962023



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2962023>

VARIOFACE output module, with plug-in bases for 16 miniature relays, 1 PDT each, for 24 V DC (without relays), with additional N and PE connection terminal blocks



Commercial data	
GTIN (EAN)	 4 017918 087081
Note	Made-to-order
sales group	I640
Pack	1 pcs.
Customs tariff	85364190
Catalog page information	Page 255 (IF-2009)

### Product notes

WEEE/RoHS-compliant since:  
09/04/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Input data</b>	
Nominal input voltage $U_N$	24 V DC (Related to the assembly)
Type of protection	Free-wheeling diode
Protective circuit/component	Damping diode

---

Operating voltage display	Green LED
Status display/channel	Yellow LED

**Output data**

Contact type	1 N/O contact
Maximum switching voltage	250 V AC/DC
Limiting continuous current	4 A
Max. total current (N)	14 A

**General data**

No. of channels	16
	32
Compatible components	Miniature relay, REL-MR- 24DC/21HC
With components	No
Width	267 mm
Height	111.5 mm
Depth	59 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Test voltage	2.5 kV (50 Hz, 1 min.)
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Mounting position	Any
Assembly instructions	In rows with zero spacing
Pollution degree	2
Surge voltage category	III
Housing insulation material	PVC, side panel PA non-reinforced,
Color	green

**Connection data**

Connection 1	Coil side
Connection method	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of positions	50
Connection 2	Contact side
Connection method	Screw connection
Number of positions	6

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Screw thread	M3
Stripping length	8 mm

### Certificates / Approvals



Certification


GOST

### Additional products

Item	Designation	Description
<b>General</b>		
2962036	UM-16 RELS/KSR-G24/1/NPE/ E/PLC	VARIOFACE output expansion module, with plug-in bases for 16 miniature relays, 1 PDT each, for 24 V DC (without relays), with additional N and PE connection terminal blocks

### Diagrams/Drawings

Circuit diagram



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;