

AI 16 -12 GN


Order No.: 3201152

The figure shows the version AI 0,75-8 GY

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3201152>

Ferrule, Length: 24 mm, Color: green

Commercial data

GTIN (EAN)	
sales group	B250
Pack	100 pcs.
Customs tariff	85369010
Catalog page information	Page 307 (CL2-2011)

Product notes

WEEE/RoHS-compliant since:
01/01/2005

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Length (b)	24 mm
Color	green
Material	E-CU
Sleeve length	12 mm
Inner dimension of the insulating collar (d)	8.8 mm

Ferrule diameter	5.8 mm
Insulating collar thickness	0.4 mm
Sleeve wall thickness	0.2 mm

Certificates / Approvals




Certification

CSA, CSAus-COMP

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;