


AI 1,5 - 8 BK-B

Order No.: 3201398


The illustration shows version AI 1,5 - 8 in red



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3201398>

Ferrules, 0.5 mm², taped, sleeve length: 8 mm, with plastic collar, galvanically tin-plated, color: black, color range according to DIN 46228-4, CSA-certified

Commercial data

GTIN (EAN)	 4 017918 094898
sales group	B256
Pack	1000 pcs.
Customs tariff	85369010
Catalog page information	Page 335 (CL2-2011)

Product notes

WEEE/RoHS-compliant since:
01/01/2005



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Length (b)	14 mm
Color	black
Material	E-CU
Sleeve length	8 mm

Inner dimension of the insulating collar (d)	3.4 mm
Ferrule diameter	1.8 mm
Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm

Certificates / Approvals




Certification

CSA, CSAus-COMP

Diagrams/Drawings

Dimensioned drawing



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;