Material			High Conductivity Seamless Copper Tube					
Plating			Electro-Tin			38 R Ref		
Wire Size			1/0 AWG	Color coded				
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric				barrel markings	
Wire Strip Length			1.0 in.		PANDUIL NOTE PAZ (72)			
Stud Size			1/4 in.	.76±.04	Z	A A N A S S S S S S S S S S S S S S S S		
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.32±.04 —		.27±.02 DIA		
UL Temperature Rating			90° C		1.95±.06			
C.S.A Certified Wire Connector			Yes					
Panduit Color Code on Barrel		ode	PINK	.94±.04 ————————————————————————————————————				
Panduit Die Index No. on Barrel		x No.	P42					
Alternate Industry Die Index No. () on Barrel		у	(12)	Wire inspec	tion wind	ow — wo		
	(®		<u>↓</u>	.39±.01 .52±.01			
	CE	RTIFIEC	LISTED Wire Connector		.12±.01			
						PANDU	CORP. TINLEY PARK, ILLINOI	
							LCA1/0-14-X	
0 9/02	SAB	DRL	RELEAS	ĒD	10318	Copper Lug	g - One-Hole, Standard Barrel	