



### FEATURES:

- This retractable sheath banana plug has a stacking feature allowing the insertion of standard or other retractable plugs

### MATERIALS:

1<sup>st</sup> End – Retractable Sheath Banana Plug

Spring – Beryllium Copper per QQ-C-533, Alloy 172, Cond. HT.

Plug Body – Brass per QQ-B-626, Alloy 360, ½ hard

Compression Spring – Stainless Steel, Alloy 302

Finish: Spring and Plug Body – Nickel plated per QQ-N-290, Class 2, 200/300 microinches.

Insulation: Polypropylene molded to plug body and wire

Color matches color of wire. Marking: POMONA

Wire: 18 AWG., stranding 65 x 36 T.C., PVC insulation. 3.66 (.144) O.D.

Marking: 5403-\*

Conn: 2<sup>nd</sup> End – Same as first end

### RATINGS:

Operating Temperature: +55°C (+131°F) Max.

Operating Voltage: 1200V AC/DC Max.

Current: 7 Amperes

### ORDERING INFORMATION: Model 5403-XX-\*

XX – Length in Inches, 12", 24", 36", 48", 60"

\* = Color Code, -0 Black and -2 Red

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA