



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: B055-001-USB-V2

### USB Virtual Media Server Interface Module for NetDirector Multi-User Cat5 IP KVM Switches

#### Highlights

- Connects a USB server to the B064-016-02-IPG NetDirector Cat5 IP KVM switch via Cat5e cable
- Use where Virtual Media access is needed on a server
- Allows a maximum distance of 40 meters (130ft ) from KVM to Server via Cat5 cable
- Compact and lightweight design
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases



#### Description

Tripp Lite's USB Virtual Media Server Interface Module connects to the USB ports on a Server, and converts them to a single RJ45 connector. Use this adapter in place of standard USB adapters if Virtual Media access is required. Ordinary Cat5e patch cables can then be used to connect the server to the switch ports on a Tripp Lite B064-016-02-IPG NetDirector Cat5 IP KVM switch. Use of Cat5e cables frees up space in the server cabinet that would be filled by traditional, thicker KVM cables. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

#### System Requirements

- Server or CPU with HD15 and USB type A connectors
- A B064-016-02-IPG NetDirector Cat5 IP KVM Switch
- Cat5e/6 cable

#### Package Includes




- USB Virtual Media Server Interface Module

#### Features

- Virtual Media Support
- Auto Signal Compensation (ASC), no DIP switch setting needed for the different distances
- Keyboard and mouse emulation - keeps your server functioning smoothly when it is disconnected from the switch's KVM port or relocated to different KVM port
- Lifetime firmware upgrades
- Superior video quality - supports resolution of up to 1600 x 1200 within the distance of up to 40m
- Built in ASIC for greater reliability and compatibility
- Compact size
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

#### Specifications

---

OVERVIEW	
Application	Connect a USB computer/server to a <a href="#">B064-016-02-IPG</a> NetDirector Cat5 IP KVM Switch using Cat5e cable
Model Type	Interface Modules
CONNECTIONS	
Connector A	 RJ45 (FEMALE)
Side B - Connector 1	 HD15 (Male)
Side B - Connector 2	 USB A (Male)
WARRANTY	
Product Warranty Period (International)	1-year limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
KVM Switches & Accessories	<a href="#">B051-000</a>	KVM Switch Accessories - IP Remote Access Unit	-
Patch Cables	<a href="#">N001-003-GY</a>	3-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Patch Cables	<a href="#">N001-010-GY</a>	10-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4473](http://www.tripplite.com/en/products/model.cfm?txtModelID=4473).

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.