



PLT1M-C702Y




- UL Listed for use in plenum or air handling spaces per NEC, Section 300-22 (C) and (D)
- Low smoke density and excellent flammability rating of UL94V-0
- Commonly accepted solution for bundling qualified cable without conduit in air handling space applications
- Applications include nuclear plants, chemical environments, telecommunications equipment, aerospace, and high and low temperature environments
- Distinctive Maroon color identifies material
- Greater resistance to damage caused by ultraviolet light – indoor or outdoor use

HALAR[®] is a registered trademark of Solvay Solexis, Inc.

▪ Part Number	PLT1M-C702Y
▪ RoHS Compliancy Status	Compliant
▪ Note	PLT1M-C702Y replaces PLT1M-C702
▪ Part Description	Cable Tie, 4.0", Miniature cross section
▪ Product Type	Cable Ties
▪ Material	HALAR Fluoropolymer
▪ Color	Maroon
▪ CSA Certified	Yes
▪ UL Listed (File #E56854)	Yes
▪ UL Recognized (File #E56854)	Yes
▪ Length (In.)	4.0
▪ Length (mm)	102
▪ Width (In.)	.098
▪ Width (mm)	2.5
▪ CE Compliant	Yes
▪ Cross Section	Miniature
▪ Head Height (In.)	.186
▪ Head Height (mm)	4.7
▪ Head Width (In.)	.188
▪ Head Width (mm)	4.8
▪ Locking Style	Locking
▪ Material Flammability Rating	UL 94V-0
▪ Max. Bundle Diameter (In.)	.87
▪ Max. Bundle Diameter (mm)	22
▪ Max. Continuous Use Temperature	302°F (150°C)
▪ Min. Loop Tensile Strength (Lbs.)	18

• Min. Loop Tensile Strength (N)	80
• Pricing Description	Cable Tie, 4.0"L (102mm), Miniature, Halar, Maroon
• Thickness (In.)	.043
• Thickness (mm)	1.1
• Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
• Min. Order UOM	PC
• Min. Order Qty.	100
• BOM Qty. (# of Pkgs.)	

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT * PART NO.	BUNDLE DIA.		A	B	C	D	E	F	MIN. LOOP TENSILE lbs. (N)	CROSS SECTION	WEIGHT lbs./100 pcs. (g)
	MIN. in (mm)	MAX. in (mm)									
PLT1M-702Y	.24 (6.1)	.87 (22)	.043 (1.1)	.098 (2.5)	.159 (4.0)	.186 (4.7)	.188 (4.8)	4.0 (102)	18 (80)	MINIATURE	.10 (45)
PLT2S-702Y	.24 (6.1)	1.88 (48)	.055 (1.4)	.190 (4.8)	.260 (6.6)	.240 (6.1)	.320 (8.1)	7.40 (188)	50 (222)	STANDARD	.49 (222)
PLT3S-702Y	.39 (10)	3.00 (76)	.055 (1.4)	.190 (4.8)	.260 (6.6)	.240 (6.1)	.320 (8.1)	11.60 (295)	50 (222)	STANDARD	.76 (344)

NOTES:

- *1) SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE.
- 2) MATERIAL HAS A UL RELATIVE THERMAL INDEX RATING OF 302°F (150°C).
- 3) MATERIAL FLAMMABILITY RATING: UL94V-0.
- 4) EXCELLENT RESISTANCE TO MOST CHEMICALS.

W10001C0/10-SS-18060

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

PANDUIT CORP. TINLEY PARK, ILLINOIS

PAN-TY CABLE TIES
PLT PLENUM WIRING SERIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± (.XXX) ± .020(.51)
(.XX) ± .021(.51) ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
C. HARVELL

MAT'L:
HALAR
FLUOROPOLYMER
COLOR: MAROON

SCALE
NONE

DATE
08/07/91

REGISTERED TRADEMARK OF
Solvay Solexis, Inc.

DRAWING NO.
SS-18060

DWG
SIZE
A

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP
10	3/24/08	JABO		CHANGED MIN BUNDLE DIA ON ALL PARTS	SS-18060	10		