



## BT2M-C




- For indoor use
- Dome-top head features unique patented design with round, smooth edges
- Stainless steel locking barb provides consistent performance, reliability and infinite adjustability through entire bundle range
- High strength and low thread force
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation (Light-Heavy cross section ties have a straight tip)

▪ Part Number	BT2M-C
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Cable Tie with metal barb, 7.9", Miniature cross section
▪ Product Type	Cable Ties
▪ Material	Nylon 6.6
▪ Color	Natural
▪ CSA Certified	Yes
▪ UL Listed (File #E56854)	Yes
▪ UL Recognized (File #E56854)	Yes
▪ Length (In.)	7.9
▪ Length (mm)	201
▪ Width (In.)	.095
▪ Width (mm)	2.4
▪ CE Compliant	Yes
▪ Cross Section	Miniature
▪ Head Height (In.)	.156
▪ Head Height (mm)	4.0
▪ Head Width (In.)	.182
▪ Head Width (mm)	4.6
▪ Locking Style	Locking
▪ Material Flammability Rating	UL 94V-2
▪ Max. Bundle Diameter (In.)	2.00
▪ Max. Bundle Diameter (mm)	51
▪ Max. Continuous Use Temperature	185°F (85°C)
▪ Min. Loop Tensile Strength (Lbs.)	18

▪ Min. Loop Tensile Strength (N)	80
▪ Pricing Description	Cable Tie, Metal Barb, 7.9"L (201mm), Miniature, Nylon, Natural
▪ Thickness (In.)	.046
▪ Thickness (mm)	1.2
▪ Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
▪ Min. Order UOM	PC
▪ Min. Order Qty.	100
▪ BOM Qty. (# of Pkgs.)	

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



PANDUIT PART NO.	BUNDLE DIA.		A	B	C	D	E	F	MIN. LOOP TENSILE lbs. (N)	CROSS SECTION	WEIGHT lbs./100 pcs. (g)
	MIN. in (mm)	MAX. in (mm)									
BT1M	.06 (1.5)	0.90 (23)	.036 (0.9)	.095 (2.4)	.110 (2.8)	.156 (4.0)	.172 (4.4)	4.0 (102)	18 (80)	MINIATURE	.05 (22)
BT1.5M	.06 (1.5)	1.5 (38)	.046 (1.2)	.095 (2.4)	.125 (3.2)	.156 (4.0)	.182 (4.6)	6.3 (160)	18 (80)	MINIATURE	.09 (43)
BT2M	.06 (1.5)	2.0 (51)	.046 (1.2)	.095 (2.4)	.125 (3.2)	.156 (4.0)	.182 (4.6)	7.9 (201)	18 (80)	MINIATURE	.12 (53)
BT4M	.06 (1.5)	4.00 (102)	.046 (1.2)	.095 (2.4)	.125 (3.2)	.156 (4.0)	.182 (4.6)	14.2 (361)	18 (80)	MINIATURE	.21 (93)

DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS

**PANDUIT** CORP. TINLEY PARK, ILLINOIS  
 DOME-TOP Barb Ty CABLE TIES  
 BT SERIES

UNLESS OTHERWISE SPECIFIED,  
 DIMENSIONAL TOLERANCES ARE:  
 (.X) ± .10(2.5)(.XXX) ± .02(0.51)  
 (.XX) ± .02(0.5) ANGLES ±

UNLESS OTHERWISE SPECIFIED,  
 ALL DIMENSIONS ARE GIVEN  
 IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY  
 PMH

MAT'L:

SCALE  
 NONE

10	5/2/06	JABO	
REV	DATE	BY	CHK

REMOVED STRAIGHT TIP REFERENCE &  
 TIP STYLE COLUMN

0037	10		
ECN	R	CUST	SUP

DATE  
 6-24-93  
 CHK'D  
 JVL

NYLON 6.6

DRAWING NO.  
 BT-0037  
 SHEET 1 OF 3

DWG  
 A  
 SIZE