



## PRT1.5S-C



- For indoor use
- Extended release tab permits easy release and re-use where changes are anticipated during development, production or servicing in the field
- To release, grasp the head of the cable tie, deflect release tab, and pull the cable tie away from the bundle
- One-piece construction for consistent performance and reliability
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation (Light-Heavy cross section ties have a straight tip)

• Part Number	PRT1.5S-C
• RoHS Compliancy Status	Compliant
• Part Description	Cable Tie, Releasable, 6.3", Standard cross section
• Product Type	Cable Ties
• Material	Nylon 6.6
• Color	Natural
• CSA Certified	Yes
• UL Listed (File #E56854)	Yes
• UL Recognized (File #E56854)	Yes
• Length (In.)	6.3
• Length (mm)	160
• Width (In.)	.190
• Width (mm)	4.8
• CE Compliant	Yes
• Cross Section	Standard
• Head Height (In.)	.219
• Head Height (mm)	5.6
• Head Width (In.)	.316
• Head Width (mm)	8.0
• Locking Style	Releasable
• Material Flammability Rating	UL 94V-2
• Max. Bundle Diameter (In.)	1.50
• Max. Bundle Diameter (mm)	38
• Max. Continuous Use Temperature	185°F (85°C)
• Min. Loop Tensile Strength (Lbs.)	50
• Min. Loop Tensile Strength (N)	222

• Pricing Description	Cable Tie, Releasable, 6.3"L (160mm), Standard, Nylon, Natural
• Thickness (In.)	.052
• Thickness (mm)	1.3
• Tool	Hand install only
• Min. Order UOM	PC
• Min. Order Qty.	100
• BOM Qty. (# of Pkgs.)	

