



## SST4H-L



- For indoor use
- Used for normal bundling and through-panel applications
- Small head height allows more efficient use of space in compact areas
- Exclusive two-piece design offers the lowest threading force in the industry
- Average 14% lighter than one-piece cable ties
- Releasable prior to final tensioning for bundle modifications
- Straight Tip design

Part Number	SST4H-L
RoHS Compliancy Status	Compliant
Part Description	Cable Tie, Releasable, 14.8", Light-Heavy cross section
Product Type	Cable Ties
Material	Nylon 6.6
Color	Natural
CSA Certified	Yes
Mil. Std. Part Number	MS3367-3-9
UL Listed (File #E56854)	No
UL Recognized (File #E56854)	Yes
Length (In.)	14.8
Length (mm)	376
Width (In.)	.300
Width (mm)	7.6
CE Compliant	Yes
Cross Section	Light-Heavy
Head Height (In.)	.325
Head Height (mm)	8.3
Head Width (In.)	.460
Head Width (mm)	11.7
Locking Style	Releasable
Material Flammability Rating	UL 94V-2
Max. Bundle Diameter (In.)	4.00
Max. Bundle Diameter (mm)	102
Max. Continuous Use Temperature	185°F (85°C)
Min. Loop Tensile Strength (Lbs.)	120

• Min. Loop Tensile Strength (N)	534
• Pricing Description	Cable Tie, 2-Piece, 14.8"L (376mm), Light-Heavy, Nylon, Natural
• Thickness (In.)	.067
• Thickness (mm)	1.7
• Tool	GTH, GS4H, GS4EH, PTH, STH2, ST3EH
• Min. Order UOM	PC
• Min. Order Qty.	50
• BOM Qty. (# of Pkgs.)	

