


THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.
© 2003, Projects Unlimited Inc.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
RATED VOLTAGE (SQUARE WAVE)	3.6	Vp-p
OPERATING VOLTAGE RANGE	2.5 ~ 4.5	Vp-p
RATED CURRENT (MAX)	90	mA
COIL RESISTANCE	15±3	OHM
MINIMUM SPL @ 10 CM	87	dB
RESONANT FREQUENCY	2,700	Hz
OPERATING TEMPERATURE	-30 ~ +70	°C
STORAGE TEMPERATURE	-40 ~ +85	°C
HOUSING MATERIAL	LCP 6130	-
TERMINAL MATERIAL	PBS	-
WEIGHT	0.42	grams

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED
-	RELEASED FROM ENGINEERING	7/27/98	
A	REVISED BOTTOM VIEW	7/31/99	S. J.
B	ADDED ELECTRICAL SPECIFICATION	6/13/02	S. J.
C	REDREW ENTIRE DRAWING	11/15/02	S. J.
D	REVISED TO NEW TEMPLATE	6/3/04	R. W.



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.

FILE NAME
SMT-9403D.DWG

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS; TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.

APPROVALS	DATE
DRAWN TMM	7/98
APPROVED S. J.	7/98
DO NOT SCALE DRAWING	

projects® unlimited Dayton, Ohio

SURFACE MOUNT TRANSDUCER
SMT-9403D

SIZE A DRAWING NO.
SMT-9403D

SCALE: N.T.S.

SHEET 1 OF 1