

Accessories - Power Outlet Strips

**Surge Suppressed Power Outlet Strip**




***Design Features***

Provides protection to data or word processing equipment and other sensitive electrical equipment from sudden spikes or high energy voltage. Prevents equipment damage, lost or distorted data. Maximum surge current is 13000 amps, response time is < 5ns. 15 amp thermal type, circuit breaker with reset. 14 gauge, 3 wire, 6 foot power cord, all components U. L. approved.

| Surge Suppressed Power Outlet Strips |  |                |        |             |
|--------------------------------------|--|----------------|--------|-------------|
| Catalog Number                       |  | No. of Outlets | Length | Weight Lbs. |
| POS-4-S                              |  | 4              | 17.50" | 2.00        |
| POS-66                               |  | 6              | 12.25" | 1.75        |
| POS-7-S                              |  | 7              | 48.00" | 3.50        |
| POS-9-S                              |  | 9              | 60.00" | 4.25        |
| POS-11-S                             |  | 11             | 72.00" | 4.75        |

PART NAME: POWER OUTLET STRIP | PART No.: POS-4-S TO POS-66



| PART NO. | QTY. OF<br>OUTLETS | SURGE<br>SUPPRESSED | A      | B     | C                            | D     | E     | F     | G     | H     | QTY. OF<br>MTG. CLIPS |
|----------|--------------------|---------------------|--------|-------|------------------------------|-------|-------|-------|-------|-------|-----------------------|
| POS-4-S  | (4)                | YES                 | 17.625 | 0.938 | (3) SPACES @ 3.062 = 9.188   | 3.062 | 2.000 | 1.750 | 2.093 | 2.000 | (2)                   |
| POS-6    | (6)                | NO                  | 12.250 | 0.969 | (5) SPACES @ 1.250 = 6.250   | 1.250 | 1.828 | 1.563 | 1.843 | 1.750 | (2)                   |
| POS-7-S  | (7)                | YES                 | 48.125 | 4.625 | (6) SPACES @ 6.000 = 36.000  | 6.000 | 2.000 | 1.750 | 2.093 | 2.000 | (2)                   |
| POS-9-S  | (9)                | YES                 | 60.125 | 4.625 | (8) SPACES @ 6.000 = 48.000  | 6.000 | 2.000 | 1.750 | 2.093 | 2.000 | (3)                   |
| POS-11-S | (11)               | YES                 | 72.125 | 4.625 | (10) SPACES @ 6.000 = 60.000 | 6.000 | 2.000 | 1.750 | 2.093 | 2.000 | (3)                   |
| POS-66   | (6)                | YES                 | 13.000 | 0.969 | (5) SPACES @ 1.250 = 6.250   | 1.250 | 2.000 | 1.750 | 2.093 | 2.000 | (2)                   |