



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: B060-016-2

KVM Switch - 16-Port (2-User) 1U Rackmount Cat5 Matrix KVM Switch

Highlights

- Two consoles independently and simultaneously control up to 16 directly connected computers, or over 1,000 when additional KVMs are connected
- Multi-platform support: PC, Sun or Mac
- Rackmountable in a 1U design...Rackmount Hardware Included
- Inexpensive Cat5 cabling makes cable management a breeze; up to 500 ft. distance from console to switch and up to 500 ft. from switch to servers
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases



Description

Tripp Lite's 2-User 16-port NetDirector® 1U Rackmount Matrix KVM Switch is the optimal solution for controlling multiple computers (combination of PS/2, USB or Sun) by two independent, simultaneous users. A single unit occupies a mere 1U of rack space, yet can control up to 16 directly connected computers. A maximum of 1,024 computers can be connected through a combination of daisy-chaining and cascading. RJ45 connections allow signals to travel up to 150 meters away (500 ft.) using ordinary Cat5 cable, while maintaining video resolution. Use either PS/2 or USB console equipment to connect to PS/2, USB or SUN Servers.

For Government purchasers, B060-016-2 is Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

System Requirements

- Console: The Tripp Lite [B062-002-PS2](#) or [B062-002-USB](#) Console Interface Module must be used to connect a console (Keyboard, Monitor and Mouse) to the KVM switch
- Computers: The Tripp Lite [B054-001-SUN](#), [B054-001-PS2](#) or [B054-001-USB](#) Server Interface Module must be used to connect a computer/server to the KVM switch

Package Includes

- 1 - B060-016-2 KVM Switch
- 1 - Power Cord
- 1 - Daisy Chain Cable
- 1 - CD with Owner's Manual
- 1 set - Rackmount Hardware

Features

- Three Level password security: Super Administrator, Administrator, and Users
- Superior video quality - up to 1024 x 768 @ 60Hz at 500ft.
- Auto Signal Compensation (ASC) assures optimum video resolution for distances up to 500ft between the switch and the consoles or computers - no dip switch setting required
- PS/2 keyboard and mouse emulation - computers boot even when the console focus is elsewhere. Keep Alive feature ensures that the keyboard and mouse work properly even if the switch temporarily loses power

- Daisy chain up to 7 additional B060-016 KVM Switches
- No software required; convenient computer selection via intuitive hotkey combinations or On Screen Display (OSD) menus
- OSD port list automatically expands when stations are added - port names are automatically reconfigured when the station sequence is changed
- OSD screen automatically adjusts to resolution changes
- Hot pluggable; add or remove components without having to power off the switch
- USB & PS/2 Consoles can control any combination of USB, PS/2, or SUN computers
- LCD, VGA, SVGA, XGA, and MultiSync support; DDC2B
- Rackmount Hardware Included
- Lifetime firmware upgrading via flash ROM
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
# Of Users	2
Console	No
Port Control	Hotkeys, OSD
Max CPU	1024
PC/Server	VGA, USB or PS/2
Cat5 KVM Switch	Yes
IP Remote Access	YES WITH B051-000
PHYSICAL	
Color	Black
Style	1U Rackmount
LCD Monitor (in.)	Not Applicable
CONNECTIONS	
Ports	16
FEATURES/SPECIFICATIONS	
BTUs	38.6 to 41.7

Related Items

Required Products

Product Type	Related Model	Description	Qty.
KVM Switches & Accessories	B054-001-SUN	KVM Switch Accessories - SUN Server Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B062-002-PS2	KVM Switch Accessories - PS/2 Console Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B054-001-PS2	KVM Switch Accessories - PS/2 Server Interface Module for NetDirector Matrix KVM Switches	1
KVM Switches & Accessories	B054-001-USB	KVM Switch Accessories - USB Server Interface Module for NetDirector Matrix KVM Switches	1

Optional Products

Product Type	Related Model	Description	Qty.
--------------	---------------	-------------	------

Rackmount Consoles	N001-025-GY	25-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Cables and Accessories	P770-013	13-ft. KVM Switch Daisychain Cable for B060 KVMs	-
Cables and Accessories	P770-10M	33-ft. (10M) KVM Switch Daisychain Cable for B060 KVMs	-
KVM Switches & Accessories	B051-000	KVM Switch Accessories - IP Remote Access Unit	-
Rackmount Consoles	N001-100-GY	100-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-050-GY	50-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
KVM Switches & Accessories	B021-000-17	Rackmount Console - 1U Rackmount Console with 17" LCD	-
Rackmount Consoles	N001-003-GY	3-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Rackmount Consoles	N001-005-GY	5-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-
Extended Warranties	WEXT3-KVM-RMNC	3-Year Extended Warranty for B060-016-2 KVM Switch	-
Extended Warranties	WEXT5-KVM-RMNC	5-Year Extended Warranty for B060-016-2 KVM Switch	-
Rackmount Consoles	N001-007-GY	7-ft. Cat5e 350MHz Snagless Molded Cable (RJ45 M/M) - Gray	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3690.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.