

# Protect Fuses from Extreme Conditions

## Gasket-sealed, In-line Fuse Holders Seal out Contaminants, Seal in the Power

#### **Superior Seal**

Tough cover locks tightly to fuse holder, silicone rubber gasket provides excellent seal

#### **Water and Solvent Resistant**

Black nylon housing and PVC insulated leads are highly resistant to attack from water, common solvents and harsh environments

#### **Wide Range of Applications and Demand**

Ideal for SUV, ATV, trailer and marine applications where water and contamination of fuse holders are a problem

#### Handle up to 30 Amps

Five-inch, 12-gauge copper leads come fully assembled, ready for splicing into circuits

#### **Easy, Secure Mounting**

Single, built-in mounting hole provides quick and secure installation

#### **Broad Market Coverage with Just Two Holders**

New HHU ATM® fuse holder complements the existing HHR ATC® holder for broad and popular blade-type fuse coverage





# **Gasket-Sealed Inline Blade Fuse Holders**



Standard Retail

#### **New HHU for ATM® Blade Fuses**

#### **Specifications**

**PVC** insulated

Max

60


60

6

6

red

Volts: Up to 32Vdc Cap & Housing: Nylon Gasket: Silicone Rubber Lead Wires: (2) 12-gauge; 5", silicone coated and Amps: Up to 30A Flammability Rating: UL 94V2 Terminals: Tin-plated brass Available in blister or boxed packaging



|        | Unit   |        |     |                | Shelf Carton   |     |      |                 | Master Carton  |     |                 |     |     |      |
|--------|--------|--------|-----|----------------|----------------|-----|------|-----------------|----------------|-----|-----------------|-----|-----|------|
| Part#  | UPC    | Code   | Qty | Unit<br>Weight | Bar Code       | Qty | Wgt  | Cubic<br>Inches | Bar Code       | Qty | Cubic<br>Inches | Wgt | Tie | High |
| HHU    | 051712 | 505758 | 1   | 0.05           | 30051712505759 | 10  | 0.5  | 35.25           | 70051712505757 | 320 | 1401.45         | 17  | 12  | 4    |
| BP/HHU | 051712 | 629904 | 1   | 0.06           | 30051712629905 | 5   | 0.35 | 108.74          | 70051712629903 | 120 | 3007.64         | 8.2 | 6   | 3    |

### Cooper Bussmann provides a full line of blade-style fuse holders

| Pack      | Pack      | Amps | Gauge     | Color                  | Length       | Description  |
|-----------|-----------|------|-----------|------------------------|--------------|--|
| ATC® Styl | e         |      |           |                        |              |  |
| HHC       |           |      | 3.5" each | Does not include cover |              |  |
| HHD       | BP/HHD    | 30   | 12        | yellow                 | 3.5" each    | Does not include cover   |
| HHD-C     |           |      |           |                        |              | Cover for HHC and HHD fuse holders                                 |
| HHD-12    |           |      |           |                        |              | Display contains 12 HHD fuse holders                               |
|           | BP/HHD-30 | 30   | 12        | yellow                 | 3.5" each    | Same as HHD; also includes ATC-30 fuse                             |
| HHF       | BP/HHF    | 20   | 14        | yellow                 | 3.5" each    | Splash resistant protective cover                                  |
| HHG       | BP/HHG    | 30   | 12        | yellow                 | 3.5" each    | Splash resistant protective cover                                  |
| HHR       | BP/HHR    | 20   | 12        | orange                 | 4" each      | Locking, sealed-gasket water-resistant cover with mounting hole    |
|           | BP/HHS    | 20   |           |                        | not included | Self-stripping: use #18 to #14 AWG copper wire only (not included) |
|           | BP/HHA    | 10   |           |                        |              | Add-a-line converts to 2 circuits; plugs into fuseblock            |
| ATM® Styl | е         |      |           |                        |              |  |
| HHL       | BP/HHL    | 20   | 16        | black                  | 3.5" each    | Splash resistant protective cover                                  |
| ННМ       | BP/HHM    | 30   | 12        | red                    | 3.5" each    | Splash resistant protective cover                                  |
| ННМ-В     |           | 30   | 12        | red                    | 3.5" each    | Does not include cover   |
| ннм-с     |           |      |           |                        |              | Cover only - Fits HHM and HHL fuseholders                          |
| HHU       | BP/HHU    | 30   | 12        |                        | 4" each      | Locking, sealed-gasket water-resistant cover with mounting hole    |
|           |           | 1    | 1         |                        |              | Add-a-line converts to 2 circuits; plugs into fuseblock            |



HHX

HHX-B

HHX-C

**NEW** 

5" each

Splash resistant protective cover

Cover only - Fits HHX fuseholder

Body only; does not include lead wires