

5 x 20mm Fuse Holders

HTC Panel Mount Series

Description

- For 5 x 20mm fuses
- Tin-plated brass terminals
- Shock safety of PC2
- High temperature thermoplastic meets:
 - UL 94V0
 - Glow wire test: 960°C IEC 695-2-1
- Solderability in accordance with IEC 68-2-20



Agency Information

- cURus: Guide IZLT2/IZLT8, File E14853
- VDE: HTC-35M: File 40004459, HTC-40M: File 40004458, HTC-55M: File 40004463, HTC-70M: File 40004457

Ordering

- Specify packaging and product code


Specifications

Part Number	Cap Type	Voltage Rating Vac	Current Rating (AC)		Ambient Temperature (°C)	Temperature Rise (°C)	Maximum Temperature (°C)
			UR	VDE			
HTC-35M	Threaded Cap/Carrier	250	10A	6.3A	24	43	85
HTC-40M	Screwdriver Slot	250	10A	6.3A	24	43	85
HTC-55M	Bayonet Cap/Carrier	250	10A	6.3A	24	43	85
HTC-70M	Bayonet Cap/Carrier	250	10A	6.3A	24	43	85


Dimensions - in (mm)

Drawings Not to Scale


HTC-35M




HTC-55M



HTC-40M



HTC-70M



Component	Material
Terminal	Tin-Plated Brass
Body	Thermoplastic
Cap	Thermoplastic
Nut	Polycarbonate

Packaging Code	
Packaging Code	Description
Blank	10 fuse holders packed into a carton
BK	100 fuse holders packed into a cardboard shelf package

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.