
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN. ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	-
SENSITIVITY	-46±3	dB
STANDARD OPERATING VOLTAGE	2.0	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION MAX	0.5	mA
IMPEDANCE	2.2	k0hm
SIGNAL TO NOISE RATIO	60	dB
TERMINAL	SOLDER PADS	-
INTERNAL CAPACITOR	33	pF

REVISIONS							
LTR	DESCRIPTION	DATE	APPROVED				
_	RELEASED FROM ENGINEERING	5/31/03					
Α	REDREW DRAWING & ADDED SCREEN	12/12/02	S.J.				
В	REVISED TO NEW TEMPLATE	12/22/03	R.W.				
С	REVISED INTERNAL CAPACITOR	12/13/04	R.W.				
D	REVISED DIMENSION SIZE AND STYLE	02/24/06	B. R.				



FILE NAME

POM-2246L.DWG

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3".		projects © unlimited Dayton , Ohio			
APPROVALS	DATE	ELECTRET CONDENSER MICROPHONE			:
DRAWN RABL	5/02				- 1
APPROVED S. J.	5/02	SIZE DRAWING NO.		٦	
		А	A POM-2246L		
DO NOT SCALE DR	AWING	SCALE: NITS SHEET 1 OF		SHEET 1 OF 1	

Downloaded from **Elcodis.com** electronic components distributor