
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS LINLINITED, INC. ANY USE OR REPRODUCTION. IN ANY FORM WITHOUT PRIOR WITHEN PERMISSION OF PROJECTS UNLIMITED, INC. \$2003, Projects Unlimited Inc.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	_
SENSITIVITY (0 dB=1 V/Pa)	-44±3	dB
STANDARD OPERATING VOLTAGE	2.0	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION MAX	0.5	mA
IMPEDANCE	2.2	kOhm
SIGNAL TO NOISE RATIO	60	dB
TERMINAL	SOLDER PADS	-
INTERNAL CAPACITOR	33	pF

	REVISIONS							
LTR	DESCRIPTION	DATE	APPROVED					
_	RELEASED FROM ENGINEERING	5/31/02						
Α	REDREW DRAWING & ADDED SCREEN	12/12/02). (j					
В	REVISED TO NEW TEMPLATE	1/6/04	R.W.					
С	REVISED INTERNAL CAPACITOR	12/13/04	R.W.					
D	REVISED DIMENSION SIZE AND STYLE	12/13/04	R.W.					



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.

FILE NAME POM-2244L.DWG

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3".		projects ® unlimited Dayton , Ohio					
l	APPROVALS DATE			ELECTRET CONDENSER MICROPHONE			
ſ	DRAWN RABL	5/02	5/02				
_	APPROVED S.ノ.	6/02	SIZE DRAWING NO. Δ POM — 2244				
ı			SCALE: N.T.S. SHEET 1 OF 1				
l	DO NOT SCALE DRA	AWING				SHEET 1 OF 1	