

**Dimensions mm[inch]**  
 tolerances acc. to DIN ISO 2768-m  
 Toleranzen gem. DIN ISO 2768-m

Isometric  
 Scale 2:1  
 Maßstab 2:1

**Recommended Pad Layout**  
 Dimensions: 7,4 [0,29], 1,2 [0,05], 1,3 [0,05]

**Schematic**  
 Dimensions: 2,2 max. [0,09], 0,8 max. [0,03], 1,8 max. [0,07], 6,9 max. [0,27], 5 max. [0,20], 5,5 ±0,1 [0,22 ±0,004]

**Marking**  
 Dimensions: 5 max. [0,20], 5,5 ±0,1 [0,22 ±0,004]. Includes a label for 'Gap-position'.

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In excitation (modified contact)	Reed switch modified phys. conditioned tolerance of +/- 1 AT	37		71	AT
Test equipment	Testing 100%	KMS11+AP74			
Pull-In in milliTesla (modified conta)	MS150 - phys. caused tolerance +/- 0,1mT	3		5,8	mT

Contact data 04	Conditions	Min	Typ	Max	Unit
Contact rating (> 9 AT)	Any DC combination of V & A not to exceed their individual max.'s			3	W
Switching voltage	DC or Peak AC			30	V
Switching current (> 9 AT)	DC or Peak AC			0,3	A
Carry current (> 9 AT)	DC or Peak AC			0,5	A
Contact resistance static (>9AT)	Measured with 40% overdrive Start value			200	mOhm
Insulation resistance	RH <45 %, 100 V test voltage	10			GOhm
Breakdown voltage (> 9 AT)	according to IEC 255-5	100			VDC
Operate time incl. bounce (> 9 AT)				0,2	ms
Release time	measured with no coil excitation			0,15	ms
Capacity	@ 10 kHz across open switch		0,1		pF

Special Product Data	Conditions	Min	Typ	Max	Unit
Reach / RoHS conformity				yes	

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine, duration 11ms, in 3 axis			30	g
Vibration	from 10 - 2000 Hz			20	g
Operating temperature		-40		130	°C
Storage temperature		-55		130	°C
Soldering Temperature Tsold	Reflow according IPC/JEDEC J-STD-0			260	°C
Washability				fully sealed	

General data	Conditions	Min	Typ	Max	Unit
Remark				Pick & place force should not exceed 25cN!	
Packaging				Tape & Reel per 2000 pcs. / Tray H20	