


# Model #: BP192V12-3U

# BP192V12-3U - External Battery Pack for UPS System



battery connection

• Simple installation; 3U rackmount, tower or stack adaptable

• Extends runtime of compatible Tripp Lite UPS Systems with 192VDC external

• 2-year warranty

**Highlights** 



# Description

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU5000RT4U, SU6000RT4U, SU8000RT4U, and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

• Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

Package Includes

- BP192V12-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

### **Features**

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation
- 2-year warranty

# **Specifications**

OUTPUT			
Overload protection	50A DC output fuse		
INPUT			
UPS Input cord length (ft.)	36 in./9m, 8 AWG, 3 conductor		
BATTERY			
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs		
DC system voltage (VDC)	192		
Connects to UPS via	Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)		
Typical battery lifespan	4-6 years typical (North America)		
PHYSICAL			
Shipping weight (lbs)	211.25		
Shipping weight (kg)	95.9		
Unit Dimensions (HWD/in)	5.25 x 17.5 x 28		
Unit Dimensions (HWD/cm)	13.3 x 44.5 x 71.1		
Shipping Dimensions (HWD/in)	11.25 x 31.5 x 23		
Shipping Dimensions (HWD/cm)	28.6 x 80 x 58.4		
Unit weight (lbs)	174		
Unit weight (kg)	79		
Material of construction	Black steel cabinet		
Form factors supported	3U rack/tower		
WARRANTY			
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty		
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available		

# **Related Items**

## **Optional Products**

Product Type	Related Model	Description	Qty.
Tower Stands	2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	-
Extended Warranties	WEXT3-BP192V12	3-Year Extended Warranty - For BP192V12-3U	-
Extended Warranties	WEXT5-BP192V12	5-Year Extended Warranty - For BP192V12-3U	-
Rackmount/Wallmount Kits	2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=3139.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.