SPECIFICATIONS
1503

DESCRIPTION: 0-12VDC 5A, 12VAC 5A **Power Supply**
INPUT VOLTAGE: 115, 60Hz
ENVIRONMENTAL TEMPERATURE: 25°C

OUTPUT VOLTAGE:	**Min.**	**Max.**
0-12VDC:		
Output Voltage Range	0.1V	12V
Minimum Output Voltage	0.8V,typ.	1V
Output Current	5A, typ.	

VOLTAGE REGULATION:	
Load (0-100% load)	800mV
Line (100-120VAC Variation)	100mV
Ripple & Noise	500mVp-p

12VAC:		
Output Voltage No Load	12.5V	13.5V
Output Voltage Full Load	11.5V	
Output Current	5A, typ.	
No Load Input Current		80mA
Full Load Input Current (All rated Load)		1.5A

POWER CONSUMPTION:	
Meter Accuracy	+- 2.5%FS
Ammeter	+- 2.5%FS

Fuse **3Amps**

Dimensions (W X D X H): 184 mm x 178 mm x 110 mm

Weight: 3.10 kgs

Description:
This power supply fits for any low voltage application you may have. The 1503 has a double output 12VAC/VDC along with 5Amps at both outputs, with a Voltmeter and an Ammeter.

Operation:
Plug model 1504 into an AC outlet. Turn power switch on. Adjust voltage with control knob. Connect to either 12VAC (constant) or 12VDC (variable).

Downloaded from Elcodis.com electronic components distributor

Downloaded from Elcodis.com electronic components distributor