

Product Catalog > [Transistors](#) > [Medium Power Bipolar Transistors](#) >

| | |
|------------------|--|
| Part Number | 2N4401 |
| product family | TO-92 Plastic-Encapsulate Bipolar Transistors |
| Product Polarity | NPN |
| SMD/ThroHole | Through Hole |
| VCEO | 40V |
| VCBO | 60V |
| VEBO | 6.0V |
| Ic | |
| PC | 600mW |
| HFE(min) | 80 |
| @Ic | 10mA |
| @VCE | 1.0V |
| ICBO | |
| IEBO | |
| VCE(sat) | 0.4V |
| VBE(sat) | 0.95V |
| ft | 250MHz |
| nf | |
| TON_max | |
| Package Qty | Bulk: 1k/Bag, ,100K/Ctn; T/B: 2K/Ammo Box , 20K/Ctn; |

Green/Pb Free/RoHS/REACH

- [FAQ](#)
 - [Soldering Profile](#)
 - [Tin Whisker Evaluation](#)
 - [Moisture Sensitivity Level](#)
 - [RoHS Test Report](#)
 - [PFOS&PFOA Test Report](#)
 - [Ordering Information](#)
 - [Certification of REACH Compliance](#)
 - [Certification of RoHS Compliance](#)
 - [Deca certification\(DecaBDE\)](#)
 - [MCC's EU RoHS and Green \(Halogen & Antimony Free\)](#)
 - [Parts List](#)
 - [REACH SVHC Test Report](#)
- 

2N4401

NPN General Purpose Amplifier

Features

- Through Hole Package
- Capable of 600mWatts of Power Dissipation
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL rating 1
- Marking: Type number
- Lead Free Finish/Rohs Compliant ("P" Suffix designates Compliant. See ordering information)

Electrical Characteristics @ 25°C Unless Otherwise Specified

| Symbol | Parameter | Min | Max | Units |
|----------------------------|---|-----|-----|---------|
| OFF CHARACTERISTICS | | | | |
| $V_{(BR)CEO}$ | Collector-Emitter Breakdown Voltage* ($I_C=1.0mA$, $I_B=0$) | 40 | | Vdc |
| $V_{(BR)CBO}$ | Collector-Base Breakdown Voltage ($I_C=10mA$, $I_E=0$) | 60 | | Vdc |
| $V_{(BR)EBO}$ | Emitter-Base Breakdown Voltage ($I_E=0.1mA$, $I_C=0$) | 6.0 | | Vdc |
| I_{BL} | Base Cutoff Current ($V_{CE}=35Vdc$, $V_{BE}=0.4Vdc$) | | 0.1 | μA |
| I_{CEX} | Collector Cutoff Current ($V_{CE}=35Vdc$, $V_{BE}=0.4Vdc$) | | 0.1 | μA |

ON CHARACTERISTICS

| | | | | |
|---------------|--|-----------------------------|-------------|-----|
| h_{FE} | DC Current Gain* ($I_C=0.1mA$, $V_{CE}=1.0Vdc$) ($I_C=1.0mA$, $V_{CE}=1.0Vdc$) ($I_C=10mA$, $V_{CE}=1.0Vdc$) ($I_C=150mA$, $V_{CE}=1.0Vdc$) ($I_C=500mA$, $V_{CE}=1.0Vdc$) | 20 40 80 100 40 | 300 | |
| $V_{CE(sat)}$ | Collector-Emitter Saturation Voltage ($I_C=150mA$, $I_B=15mA$) ($I_C=500mA$, $I_B=50mA$) | | 0.4 0.75 | Vdc |
| $V_{BE(sat)}$ | Base-Emitter Saturation Voltage ($I_C=150mA$, $I_B=15mA$) ($I_C=500mA$, $I_B=50mA$) | 0.75 | 0.95 1.2 | Vdc |

SMALL-SIGNAL CHARACTERISTICS


| | | | | |
|----------|--|-----|------|-----|
| f_T | Current Gain-Bandwidth Product ($I_C=20mA$, $V_{CE}=10Vdc$, $f=100MHz$) | 250 | | MHz |
| C_{cb} | Collector-Base Capacitance ($V_{CB}=5.0Vdc$, $I_E=0$, $f=100kHz$) | | 6.5 | pF |
| C_{eb} | Emitter-Base Capacitance ($V_{BE}=0.5Vdc$, $I_C=0$, $f=100kHz$) | | 30.0 | pF |

SWITCHING CHARACTERISTICS

| | | | | |
|-------|--------------|--------------------------------|-----|----|
| t_d | Delay Time | $(V_{CC}=30Vdc, V_{BE}=0.2Vdc$ | 15 | ns |
| t_r | Rise Time | $I_C=150mA, I_{B1}=15mA$) | 20 | ns |
| t_s | Storage Time | $(V_{CC}=30Vdc, I_C=150mA$ | 225 | ns |
| t_f | Fall Time | $I_{B1}=I_{B2}=15mA$) | 30 | ns |

*Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2.0\%$

TO-92



| DIM | INCHES | | MM | | NOTE |
|-----|--------|------|-------|-------|------|
| | MIN | MAX | MIN | MAX | |
| A | .170 | .190 | 4.33 | 4.83 | |
| B | .170 | .190 | 4.30 | 4.83 | |
| C | .550 | .590 | 13.97 | 14.97 | |
| D | .010 | .020 | 0.36 | 0.56 | |
| E | .130 | .160 | 3.30 | 3.96 | |
| G | .010 | .104 | 2.44 | 2.64 | |



Micro Commercial Components

Ordering Information

| Device | Packing |
|------------------|-----------------------------|
| (Part Number)-AP | Ammo Packing; 2Kpcs/AmmoBox |
| (Part Number)-BP | Bulk; 1Kpcs/Bag |