

5-1437535-4 Product Details



5-1437535-4

TE Internal Number: 5-1437535-4

 [Active](#)

SIP Sockets

 [Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- 20 Positions
- Contact Style = Stamped + Formed
- Leg Style = Standard
- Beryllium Copper Contact Base Material
- Gold (10) Contact Plating, Mating Area, Material

[View all Features](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Leg Style = Standard • Sleeve Material = Brass • Breakaway Header = Yes <p>Termination Related Features:</p> <ul style="list-style-type: none"> • Termination Post Length (mm [in]) = 3.18 [0.125] <p>Body Related Features:</p> <ul style="list-style-type: none"> • Number of Positions = 20 • Sleeve Material Plating = Gold <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Contact Style = Stamped + Formed • Contact Base Material = Beryllium Copper • Contact Plating, Mating Area, Material = Gold (10) 	<p>Housing Related Features:</p> <ul style="list-style-type: none"> • Housing Material = Thermoplastic - GF • UL Flammability Rating = UL 94V-0 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Always was RoHS compliant <p>Other:</p> <ul style="list-style-type: none"> • Brand = AMP