



1.02±.002
 .040±.002
 DIA HOLE TYP

PCB LAYOUT: COMPONENT SIDE
 RECOMMENDED PCB THICKNESS:

1.57± 0.18
 .062±.007

Above Drawing For Reference Only

Ordering Information				
Circuits	Order No.		Dimension mm (inches)	
	Tin	Gold	A (Overall Length)	B (1st to Last Ckt)
2	*22-23-2021	*22-11-2022	5.08(.200)	2.54(.100)
3	*22-23-2031	*22-11-2032	7.62(.300)	5.08(.200)
4	*22-23-2041	*22-11-2042	10.16(.400)	7.62(.300)
5	*22-23-2051	*22-11-2052	12.70(.500)	10.16(.400)
6	*22-23-2061	*22-11-2062	15.24(.600)	12.70(.500)
7	*22-23-2071	*22-11-2072	17.78(.700)	15.24(.600)
8	*22-23-2081	*22-11-2082	20.32(.800)	17.78(.700)
9	*22-23-2091	*22-11-2092	22.86(.900)	20.32(.800)
10	*22-23-2101	*22-11-2102	25.40(1.000)	22.86(.900)
11	*22-23-2111	*22-11-2112	27.94(1.100)	25.40(1.000)
12	*22-23-2121	*22-11-2122	30.48(1.200)	27.94(1.100)
13	*22-23-2131	*22-11-2132	33.02(1.300)	30.48(1.200)
14	*22-23-2141	*22-11-2142	35.56(1.400)	33.02(1.300)
15	*22-23-2151	*22-11-2152	38.10(1.500)	35.56(1.400)
Circuits	Order No.		Dimension mm (inches)	
	Tin	Gold	A (Overall Length)	B (1st to Last Ckt)
16	*22-23-2161	*22-11-2162	40.64(1.600)	38.10(1.500)
17	*22-23-2171	*22-11-2172	43.18(1.700)	40.64(1.600)
18	*22-23-2181	*22-11-2182	45.72(1.800)	43.18(1.700)
19	*22-23-2191	*22-11-2192	48.26(1.900)	45.72(1.800)

20	*22-23-2201	*22-11-2202	50.80 (2.000)	48.26 (1.900)
21	*22-23-2211	*22-11-2212	53.34 (2.100)	50.80 (2.000)
22	*22-23-2221	*22-11-2222	55.88 (2.200)	53.34 (2.100)
23	*22-23-2231	*22-11-2232	58.42 (2.300)	55.88 (2.200)
24	*22-23-2241	*22-11-2242	60.96 (2.400)	58.42 (2.300)
25	*22-23-2251	*22-11-2252	63.50 (2.500)	60.96 (2.400)
26	22-23-2261	22-11-2262	66.04 (2.600)	63.50 (2.500)
27	22-23-2271	22-11-2272	68.58 (2.700)	66.04 (2.600)
28	22-23-2281	22-11-2282	71.12 (2.800)	68.58 (2.700)

* US Standard Product available through Molex franchised distributors.

Circuit 1 designation is used to orient the header to locate the voided circuit. Review mating connector to assure correct mating orientation.