


**FEATURES**

- **Low-profile: 6 mm .236 inch**  
(Tape height: max. 6.5 mm .256 inch)
- **Tape and reel package is available as standard packing style**
- **Surge withstand between contacts and coil: 2,500 V**
- **Breakdown voltage between contacts and coil: 1,500 V**
- **Capacity: 2 A**
- **High sensitivity:**  
2 Form C; 140 mW power consumption (Single side stable type)



mm inch

**SPECIFICATIONS**

**Contact**

|  |  |   |                   |
|--|--|---|-------------------|
| Arrangement  | 2 Form C                                       |   |                   |
| Initial contact resistance, max.<br>(By voltage drop 6 V DC 1 A) | 75 mΩ  |   |                   |
| Contact material   | Gold-clad silver alloy                         |   |                   |
| Rating   | Nominal switching capacity<br>(resistive load) | 2 A 30 V DC,<br>0.5 A 125 V AC                                  |                   |
|  | Max. switching power<br>(resistive load)       | 60 W, 62.5 VA   |                   |
|  | Max. switching voltage                         | 220 V DC, 125 V AC  |                   |
|  | Max. switching current                         | 2 A   |                   |
|  | Min. switching capacity ※1                     | 10 μA 10 mV DC  |                   |
| Nominal operating power  | Single side stable                             | 140 mW (1.5 to 12 V DC)<br>200 mW (24 V DC)<br>300 mW (48 V DC) |                   |
|  | 1 coil latching                                | 70 mW (1.5 to 12 V DC)<br>100 mW (24 V DC)                      |                   |
|  | 2 coil latching                                | 140 mW (1.5 to 12 V DC)<br>200 mW (24 V DC)                     |                   |
| Expected life (min. operations)                                  | Mechanical (at 180 cpm)                        | 10 <sup>8</sup>   |                   |
|  | Electrical (at 20 cpm)                         | 2 A 30 V DC resistive   | 10 <sup>5</sup>   |
|  |  | 1 A 30 V DC resistive   | 2×10 <sup>5</sup> |
|  | 0.5 A 125 V AC resistive                       | 10 <sup>5</sup>   |                   |

**Note:**

※1 This value can change due to the switching frequency, environmental conditions, and desired reliability level, therefore it is recommended to check this with the actual load. (SX relays are available for low level load switching [10 μA 1 mV DC – 10 mA 10 V DC])

**Remarks**

- \* Specifications will vary with foreign standards certification ratings.
- \*1 Measurement at same location as "Initial breakdown voltage" section.
- \*2 By resistive method, nominal voltage applied to the coil; contact carrying current: 2 A.
- \*3 Nominal voltage applied to the coil, excluding contact bounce time.
- \*4 Nominal voltage applied to the coil, excluding contact bounce time without diode.
- \*5 Half-wave pulse of sine wave: 6 ms; detection time: 10 μs
- \*6 Half-wave pulse of sine wave: 6 ms
- \*7 Detection time: 10 μs
- \*8 Refer to 6. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT

**Characteristics**

|  |                                     |   |
|--|-------------------------------------|---|
| Initial insulation resistance*1  |                                     | Min. 1,000 MΩ (at 500 V DC)   |
| Initial breakdown voltage  | Between open contacts               | 1,000 Vrms for 1 min.<br>(Detection current: 10 mA)                   |
|  | Between contact sets                | 1,500 Vrms for 1 min.<br>(Detection current: 10 mA)                   |
| Initial surge voltage  | Between contact and coil            | 1,500 Vrms for 1 min.<br>(Detection current: 10 mA)                   |
|  | Between open contacts (10×160 μs)   | 1,500 V (FCC Part 68)   |
|  | Between contacts and coil (2×10 μs) | 2,500 V (Telcordia)   |
| Temperature rise*2 (at 20°C)   |                                     | Max. 50°C   |
| Operate time [Set time]*3 (at 20°C)  |                                     | Max. 4 ms (Approx. 2 ms)<br>[Max. 4 ms (Approx. 2 ms)]                |
| Release time [Reset time]*4 (at 20°C)  |                                     | Max. 4 ms (Approx. 1 ms)<br>[Max. 4 ms (Approx. 2 ms)]                |
| Shock resistance   | Functional*5                        | Min. 750 m/s <sup>2</sup> {75 G}                                      |
|  | Destructive*6                       | Min. 1,000 m/s <sup>2</sup> {100 G}                                   |
| Vibration resistance   | Functional*7                        | 200 m/s <sup>2</sup> {20G}, 10 to 55 Hz at double amplitude of 3.3 mm |
|  | Destructive                         | 294 m/s <sup>2</sup> {30G}, 10 to 55 Hz at double amplitude of 5 mm   |
| Conditions for operation, transport and storage*8 (Not freezing and condensing at low temperature) | Ambient temperature                 | -40°C to +85°C*3<br>-40°F to +185°F                                   |
|  | Humidity                            | 5 to 85% R.H.   |
| Unit weight  |                                     | Approx. 2 g .071 oz   |

## ORDERING INFORMATION

Ex. TQ 2 SA - L - 3V - Z

| Contact arrangement | Surface-mount availability  | Operating function   | Coil voltage (DC)                   | Packing style   |
|---------------------|---|--|-------------------------------------|---|
| 2: 2 Form C         | SA: Standard surface-mount terminal type<br>SL: High connection reliability surface-mount terminal type<br>SS: Space saving surface-mount terminal type | Nil: Single side stable<br>L: 1 coil latching<br>L2: 2 coil latching | 1.5, 3, 4.5, 5, 6, 9, 12, 24, 48* V | Nil: Tube packing<br>Z: Tape and reel packing (picked from the 6/7/8/9/10-pin side) |

\*48 V coil type: Single side stable only

Notes: 1. Tape and reel (picked from 1/2/3/4/5-pin side) is also available by request. Part No. suffix "-X" is needed when ordering. (ex.) TQ2SA-3V-X  
2. Tape and reel packing symbol "-Z" or "-X" are not marked on the relay.

## TYPES

## 1. Single side stable

| Part No.    | Nominal voltage, V DC | Pick-up voltage, V DC (max.) | Drop-out voltage, V DC (min.) | Nominal operating current, mA ( $\pm 10\%$ ) | Coil resistance, $\Omega$ ( $\pm 10\%$ ) | Nominal operating power, mW | Max. allowable voltage, V DC |
|-------------|-----------------------|------------------------------|-------------------------------|--|--|-----------------------------|------------------------------|
| TQ2SO-1.5 V | 1.5                   | 1.13                         | 0.15                          | 93.8   | 16                                       | 140                         | 2.2                          |
| TQ2SO-3 V   | 3                     | 2.25                         | 0.3                           | 46.7   | 64.3                                     | 140                         | 4.5                          |
| TQ2SO-4.5 V | 4.5                   | 3.38                         | 0.45                          | 31   | 145                                      | 140                         | 6.7                          |
| TQ2SO-5 V   | 5                     | 3.75                         | 0.5                           | 28.1   | 178                                      | 140                         | 7.5                          |
| TQ2SO-6 V   | 6                     | 4.5                          | 0.6                           | 23.3   | 257                                      | 140                         | 9                            |
| TQ2SO-9 V   | 9                     | 6.75                         | 0.9                           | 15.5   | 579                                      | 140                         | 13.5                         |
| TQ2SO-12 V  | 12                    | 9                            | 1.2                           | 11.7   | 1,028                                    | 140                         | 18                           |
| TQ2SO-24 V  | 24                    | 18                           | 2.4                           | 8.3  | 2,880                                    | 200                         | 36                           |
| TQ2SO-48 V  | 48                    | 36                           | 4.8                           | 6.3  | 7,680                                    | 300                         | 57.6                         |

## 2. 1 coil latching

| Part No.      | Nominal voltage, V DC | Set voltage, V DC (max.) | Reset voltage, V DC (max.) | Nominal operating current, mA ( $\pm 10\%$ ) | Coil resistance, $\Omega$ ( $\pm 10\%$ ) | Nominal operating power, mW | Max. allowable voltage, V DC |
|---------------|-----------------------|--------------------------|----------------------------|--|--|-----------------------------|------------------------------|
| TQ2SO-L-1.5 V | 1.5                   | 1.13                     | 1.13                       | 46.9   | 32                                       | 70                          | 2.2                          |
| TQ2SO-L-3 V   | 3                     | 2.25                     | 2.25                       | 23.3   | 128.6                                    | 70                          | 4.5                          |
| TQ2SO-L-4.5 V | 4.5                   | 3.38                     | 3.38                       | 15.6   | 289.3                                    | 70                          | 6.7                          |
| TQ2SO-L-5 V   | 5                     | 3.75                     | 3.75                       | 14   | 357                                      | 70                          | 7.5                          |
| TQ2SO-L-6 V   | 6                     | 4.5                      | 4.5                        | 11.7   | 514                                      | 70                          | 9                            |
| TQ2SO-L-9 V   | 9                     | 6.75                     | 6.75                       | 7.8  | 1,157                                    | 70                          | 13.5                         |
| TQ2SO-L-12 V  | 12                    | 9                        | 9                          | 5.8  | 2,057                                    | 70                          | 18                           |
| TQ2SO-L-24 V  | 24                    | 18                       | 18                         | 4.2  | 5,760                                    | 100                         | 36                           |

## 3. 2 coil latching

| Part No.       | Nominal voltage, V DC | Set voltage, V DC (max.) | Reset voltage, V DC (max.) | Nominal operating current, mA ( $\pm 10\%$ ) | Coil resistance, $\Omega$ ( $\pm 10\%$ ) | Nominal operating power, mW | Max. allowable voltage, V DC |
|----------------|-----------------------|--------------------------|----------------------------|--|--|-----------------------------|------------------------------|
| TQ2SO-L2-1.5 V | 1.5                   | 1.13                     | 1.13                       | 93.8   | 16                                       | 140                         | 2.2                          |
| TQ2SO-L2-3 V   | 3                     | 2.25                     | 2.25                       | 46.7   | 64.3                                     | 140                         | 4.5                          |
| TQ2SO-L2-4.5 V | 4.5                   | 3.38                     | 3.38                       | 31   | 145                                      | 140                         | 6.7                          |
| TQ2SO-L2-5 V   | 5                     | 3.75                     | 3.75                       | 28.1   | 178                                      | 140                         | 7.5                          |
| TQ2SO-L2-6 V   | 6                     | 4.5                      | 4.5                        | 23.3   | 257                                      | 140                         | 9                            |
| TQ2SO-L2-9 V   | 9                     | 6.75                     | 6.75                       | 15.5   | 579                                      | 140                         | 13.5                         |
| TQ2SO-L2-12 V  | 12                    | 9                        | 9                          | 11.7   | 1,028                                    | 140                         | 18                           |
| TQ2SO-L2-24 V  | 24                    | 18                       | 18                         | 8.3  | 2,880                                    | 200                         | 36                           |

O: For each surface-mounted terminal variation, input the following letter.

SA type: A, SL type: L, SS type: S

Notes: 1. Specified value of the pick-up, drop-out, set and reset voltage is with the condition of square wave coil pulse.

2. Standard packing: Tube: 50 pcs.; Case: 1,000 pcs.

Tape and reel: 500 pcs.; Case: 1,000 pcs.


3. In case of 5 V transistor drive circuit, it is recommended to use 4.5 V type relay.

# TQ SMD


## DIMENSIONS

mm inch


### SA type



### SL type




### SS type



General tolerance:  $\pm 0.3 \pm 0.12$


### Recommendable mounting pad (Top view)



Tolerance:  $\pm 0.1 \pm 0.04$


### Schematic (Top view)

#### •Single side stable (Deenergized condition)




\*Orientation stripe located on top of relay.

#### •1-coil latching (Reset condition)



\*Orientation stripe located on top of relay.


#### •2-coil latching (Reset condition)




\*Orientation stripe located on top of relay.

## REFERENCE DATA

### 1. Maximum switching capacity




### 2. Life curve




### 3. Mechanical life (mounting by IRS method)

Tested sample: TQ2SA-12V, 10 pcs.




### 4.-(1) Electrical life (2 A 30 V DC resistive load)

Tested sample: TQ2SA-12V, 6 pcs.  
Operating frequency: 20 cpm  
Change of pick-up and drop-out voltage (mounting by IRS method)



### Change of contact resistance (mounting by IRS method)



### 4.-(2) Electrical life (0.5 A 125 V AC resistive load)

Tested sample: TQ2SA-12V, 6 pcs.  
Operating frequency: 20 cpm  
Change of pick-up and drop-out voltage (mounting by IRS method)

