

# Steel City

**T&B Catalog Number:** NC301 UPC Number: 78599142751

**Description:** 3/8" Connector, Clamp Type, Die Cast Zinc, Non-watertight. For use with Non-

Metallic Sheathed Cable.

Status: Active

General	
Trade Size (inches)	3/8" (1/2" Knockout)
Material	Die Cast Zinc
Connection Type	Clamp
Dimension Information	
Diameter_B (inches)	1.16
A_Minimum (inches)	.18
A_Maximum (inches)	.64
Packaging	
T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	5.5 lbs. per 100
Certifications	
RoHS Compliance	Yes
Certifications	




File Nbr:

E 17583

## Steel City

## Non-Metallic Sheathed Cable Fittings

#### **NM Clamp Type** Connector — Die Cast Zinc




CAI.	CONDUIT DIMENSIONS (IN.)				
NO.	SIZE	A (MIN.)	A (MAX.)	В	CTN.
NC-201	56"	0.40	0.95	1.87	250
NC-202	35"	0.50	1.10	1.84	200
NC-203	1"	0.62	1.14	2.00	100
NC-204	150	0.50	1.38	2.28	100
NC-205	18"	0.75	1.61	2.49	50
NC-206	2"	0.90	2.04	3.35	50

CSA File No. LR-12798.

UL File No. E-17583. ......

#### Clamp Type Connector -**Die Cast Zinc**



CAT. NO.	CONDUIT DIMENSIONS (IN.)				STD.
NO.	SIZE	A (MIN.)	A (MAX.)	В	CTN.
NC301	3/" (// KO)	0.18	0.64	1.16	1,000
NC-302	30"	0.41	0.82	1.87	500
NC-303	1"	0.34	0.94	2.01	250

CSA File No. LR-12798.

UL File No. E-17583.

#### **Connectors Clamp Type,** Non-Watertight -Die Cast Zinc






₩.

CAT.	CONDUIT		STD.		
NO.	SIZE	A (MIN.)	A (MAX.)	В	CTN.
NC041	1%"	0.27	0.75	2.02	100
NC-051	195	0.54	0.95	2.50	50
NC-061	2"	0.75	1.12	3.41	40

UL File No. E-15170 - 11/6-11/6".

UL File No. E-17583 - 21.

### Duplex Clamp Type Connector Die Cast Zinc



CAT.	CONDUIT	ONDUIT DIMENSIONS (IN.)			
NO.	SIZE	A (MIN.)	A (MAX.)	В	CTN.
XC-210	3/4 (3/4 KO)	0.13	0.65	1.58	250
XC-211-SC	30"	0.24	0.63	1.59	200
XC-222-SC	30"	0.24	0.63	1.59	200

CONDUIT/CABLE	FMC	AC	MCC	MCI
Max. Size	3/2"	10/2	.565	.565
Min. Size	3/5**	14/2	.425	.425

CSA File No. LR-12798.

UL File No. E1383.


· For use with aluminum smooth extruded metal clad cable. (min. dia. .410) - (max. dia. .500).

#### NM Flex Connectors, Saddle Type — Die Cast Zinc



CAT.		DIMEN		STD.	
NO.	SIZE	A (MIN.)	A (MAX.)	В	CTN.
XC-2200-C	50"	0.12	0.63	0.98	500

#### Tilt-In Connector Metallic Steel -Electro-Galvanized



CAT.	CONDUIT	DIMENSIONS (IN.)					
NO.	SIZE	A	В	C	D	E	CTN.
NC-850	56"	.050	.960	1.312	.650	8-32 x %	1,000
NC-851	5/2-1	.050	1.250	1.750	.760	8-32 x 1	500
NC-852	1-10"	.062	1.625	2.125	.760	10-32 x 1	250
NC-853	1-16**	.062	1.970	2.500	.785	10-32 x 12	100