



Search This Product Catalog

[Product Catalog for Global Telecommunications OEM Site](#) > [Products for Equipment Manufacturers](#) > [Products for Broadband Equipment Manufacturers](#) > [Board to Board Connectors](#) > [Shunts](#) > [3M™ .100" Shunt Midgie, 929 Series](#) >

 [Printer-friendly format](#) **3M™ .100" Shunt Midgie, 929950-00**  
Color plating options black/unplated



[\[click to enlarge\]](#)

3M Id : 80-6200-8254-7  
GTIN(UPC/EAN) : 0 00 54007 85124 0

**Additional Information**

- Unique C-Spring contact insures balanced forces.
- Compatible with .025" pins.
- Stackable end-to-end and side-to-side. Color coded for easy identification

**Learn More . . .**

[Packaging Data](#)  
[3M™ .100 in. Shunt, .100" Midgie, 929 Series, TS0200 - Data Sheet \(PDF 369.5 K\)](#)

**Please Note:**  
Adobe® Acrobat® Reader is required to view PDF documents.



Return to Solutions for Network Equipment Manufacturers

- Product Catalog for Global Telecommunications OEM Site
  - Products for Business Enterprise
  - Products for Carriers
  - Products for Equipment Manufacturers

Related Solution Sites

- 3M Access Network
- Enterprise Networks

**Characteristics**

<b>Contact Material</b>	Copper Alloy
<b>Contact Underplating</b>	50 μ" [1.27 μm] Nickel
<b>Contact Wiping Area Plating</b>	None
<b>Current Rating</b>	1 Ampere
<b>Insulation Color</b>	Black
<b>Insulation Flammability Rating</b>	UL 94V-0
<b>Insulation Material</b>	Glass Filled Polyester (PBT)
<b>Insulation Resistance</b>	>5 X 109 Ohms @ 500 Vdc
<b>Interface Grid</b>	.100"
<b>Interface Style</b>	Rectangular Socket
<b>Markings</b>	3M Logo
<b>Non-Operating Temperature</b>	-55 to 100 Degree Celsius
<b>Primary Trademark Name</b>	Metpak
<b>Separable</b>	Yes
<b>Termination Style</b>	Shunted Contacts

