




Search This Product
Catalog

[Product Catalog for Access Network Solutions](#) > [Fiber Connectors, Splices, Couplings and Cable Assemblies](#) > [Fiber Connectors and Couplings](#) > [ST Connectors and Couplings](#) > [Hot Melt ST Connectors](#) >

[Printer-friendly format](#) **6100-B Connector ST MM Hot Melt Black Boot**



The Hot Melt ST* Fiber Optic Connector is a keyed bayonet style multimode/single-mode connector, compatible with ST* connectors, which incorporates 3M™ hot melt adhesive and pre-radiused PC zirconia ceramic ferrule technology.

[\[click to enlarge\]](#)

3M Id : 80-6111-2754-1
GTIN(UPC/EAN) : 0 00 54007 91142 5

Additional Information

The result is a quick mount fiber optic connector that delivers low light-loss, solid intermateability and mechanical stability, while costing less to install.

Learn More . . .

[Packaging Data](#)

[MSDS \(United States\)](#)

[Fiber Optic ST and FC Connectors - Instructions/Manual \(PDF 662.8 K\)](#)

[Hot Melt Bayonet ST Connectors Features and Benefits - Features and Benefits- \(JPG\)](#)

[SC, FC, ST Hot Melt Fiber Optic Connectors - Instructions/Manual \(PDF 534.1 K\)](#)

[ST Connector - Illustration/Line Art](#)

[ST Connector - Illustration/Line Art](#)

[ST Connector Lineart - Illustration/Line Art- \(TIFF\)](#)

[ST Connectors Lineart - Illustration/Line Art- \(TIFF\)](#)

[ST* Connectors and Accessories - Bulletin \(PDF 515.6 K\)](#)

Please Note:

Adobe® Acrobat® Reader is required to view PDF documents.



Characteristics

Boot Material	Estane
Flame Retardant	UL-94 V-O
Operating Temperature Range	-40 to 60 Degree Celsius
Primary Trademark Name	3M

Access Network Solutions

Product Catalog for Access Network Solutions

- 3M™ Dynatel™ Diagnostic Test Equipment
- Cabinets
- Copper Splicing
- Fiber and Copper Closures and Terminals
- Fiber Cable Assemblies
- **Fiber Connectors, Splices, Couplings and Cable Assemblies**
- Fiber Management Systems
- Locating and Marking Systems
- Quante Products
- Related Products

Other Tools

- Where to Buy

Storage Temperature

-40 to 85 Degree Celsius

© 3M 1995-2005

[Legal Information](#)

[Privacy Policy](#)

[Contact Us](#)

[About 3M](#)

[Search 3M](#)

[3M Worldwide](#)