



Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

| | |
|-----------------------------|--|
| Type | DPA |
| Height | 4.00 Inches |
| Depth | 3.12 Inches |
| Ampere Rating | 30A |
| Approvals | UL Listed File Number E42240 CCN NLDX; CSA Certified File Number LR25490 Class 321104; CE Marked |
| Catalog Reference Number | 8910CT9301 |
| Horsepower Rating (1-Phase) | 2HP@115VAC - 5HP@230VAC |
| Horsepower Rating (3-Phase) | 10HP@230VAC - 15HP@460/575VAC |
| Locked Rotor Amperes | 180A@230VAC - 150A@460VAC - 120A@575VAC |
| Enclosure Type | Open |
| Maximum Voltage Rating | 600VAC |
| Mounting Type | Panel |
| Number of Poles | 3-Pole |
| Operating Voltage | 120VAC@60Hz - 110VAC@50Hz |
| Phase | 3-Phase |
| Action | Non-Reversing |
| Width | 2.50 Inches |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 21343 - Contactors, Definite Purpose, 30 Amp |
| Discount Schedule | CP1B |
| Article Number | 785901073536 |
| Package Quantity | 8 |
| Weight | 1.08 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |

[document.](#)