

66428-3

TE Internal Number: 66428-3

Active

Multimate



Always EU RoHS/ELV Compliant (Statement of

Compliance)

Product Highlights:

- Socket
- Gold (15) over Nickel (50) Contact Mating Area Plating Material
- Wire Range = 0.05-0.15 [30-26] mm [AWG]
- Insulation Diameter = 1.02 1.52 mm
- Brass Contact Base Material

View all Features

Documentation & Additional Information

Product Drawings:

• SOCKET ASSEMBLY, LOOSE PIECE, TYPE III+ (PDF, English)

Catalog Pages/Data Sheets:

- HIGH CURRENT PRODUCTS (PDF, English)
- PRECISION PIN AND SOCKET CONTACTS (PDF, English)
- Signal Contacts (PDF, English)
- M_SERIES_PIN_AND_SOCKET_CONNECTORS (PDF, English)
- CIRCULAR CONNECTORS FOR COMMERCIAL SIGNAL AND POWER ... (PDF, English)
- AMP Circular Connectors for Commercial Signal & Powe... (PDF, English)

Product Specifications:

None Available

Application Specifications:

• Type III+ (Size 16) Contacts (PDF, English)

Instruction Sheets:

 <u>Selection Charts for Multimate Pin and Socket Contacts</u> (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version L)
- 3D Model (IGES, Version L)
- 3D Model (STEP, Version L)

List all Documents

Additional Information:

• Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- <u>Pin/Socket</u> = Socket
- <u>Insulation Diameter (mm [in])</u> = 1.02 1.52
 [0.040 0.060]
- Product Type = Type III+
- Insulation Support = Yes
- Wire Termination Type = Crimp
- Wire/Cable Type = Discrete Wire
- Grade = Commercial
- Comment = Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [.125].; Insertion Tool No. 91002-1 (for Insulation Dia. 1.78 [.070] or less), No. 200893-2 (for Insulation Dia. .090 [2.29] max.) Extraction Tool No. 305183.

Electrical Characteristics:

Contact Related Features:

- <u>Contact Mating Area Plating Material</u> = Gold
 (15) over Nickel (50)
- <u>Contact Base Material</u> = Brass
- Contact Size = 16
- Contact Type = Signal

Industry Standards:

- <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

• Terminate To = Wire

• High Current = No

Termination Related Features:

- <u>Termination End Plating</u> = Gold Flash
- Pin Diameter (mm [in]) = 1.57 [0.062]

Body Related Features:

- Wire Range (mm [AWG]) = 0.05-0.15 [30-26]
- Spring Material = Stainless Steel
- Used With = M Series Connectors, CPC Connectors

• Test Current (Amps.) = 13.0

Packaging Related Features:

• Packaging Method = Loose Piece

Other:

• Brand = AMP