8910DPA63V02

Definite Purpose Contactor , Non-Reversing, 60A, 3-Phase, 3-Pole





Technical Characteristics

Ampere Rating 60A Approvals UL Listed - CSA Certified - CE Marked Horsepower Rating (1-Phase) 5HP@115VAC - 10HP@230VAC Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 3-Pole Locked Rotor Amperes 360A@230VAC - 300A@460VAC - 240A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches		
Approvals Approvals Horsepower Rating (1-Phase) Maximum Voltage Rating Mounting Type Mounting Type Panel Number of Poles Locked Rotor Amperes Action Action Non-Reversing Type DPA Depth Height Locked Rating UL Listed - CSA Certified - CE Marked Locked Rotor Amprecal Multipe (1-Phase) Action Non-Reversing UL Listed - CSA Certified - CE Marked Locked Rotor Amprecal Multipe (230VAC) Movaca Action Non-Reversing DPA Action Depth 4.06 Inches	Enclosure Type	Open
Horsepower Rating (1-Phase) Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles Locked Rotor Amperes 360A@230VAC - 300A@460VAC - 240A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase Action Non-Reversing Type DPA Depth Height 4.06 Inches	Ampere Rating	60A
Maximum Voltage Rating600VACMounting TypePanelNumber of Poles3-PoleLocked Rotor Amperes360A@230VAC - 300A@460VAC - 240A@575VACHorsepower Rating (3-Phase)25HP@230VAC - 30HP@460/575VACOperating Voltage120VAC@60Hz - 110VAC@50HzPhase3-PhaseActionNon-ReversingTypeDPADepth3.67 InchesHeight4.06 Inches	Approvals	UL Listed - CSA Certified - CE Marked
Mounting Type Panel Number of Poles 3-Pole Locked Rotor Amperes 360A@230VAC - 300A@460VAC - 240A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Horsepower Rating (1-Phase)	5HP@115VAC - 10HP@230VAC
Number of Poles 3-Pole Locked Rotor Amperes 360A@230VAC - 300A@460VAC - 240A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Maximum Voltage Rating	600VAC
Locked Rotor Amperes 360A@230VAC - 300A@460VAC - 240A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Mounting Type	Panel
Horsepower Rating (3-Phase) 25HP@230VAC - 30HP@460/575VAC Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Number of Poles	3-Pole
Operating Voltage 120VAC@60Hz - 110VAC@50Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Locked Rotor Amperes	360A@230VAC - 300A@460VAC - 240A@575VAC
Phase 3-Phase Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Horsepower Rating (3-Phase)	25HP@230VAC - 30HP@460/575VAC
Action Non-Reversing Type DPA Depth 3.67 Inches Height 4.06 Inches	Operating Voltage	120VAC@60Hz - 110VAC@50Hz
Type DPA Depth 3.67 Inches Height 4.06 Inches	Phase	3-Phase
Depth 3.67 Inches Height 4.06 Inches	Action	Non-Reversing
Height 4.06 Inches	Туре	DPA
	Depth	3.67 Inches
Width 2.56 Inches	Height	4.06 Inches
	Width	2.56 Inches

Shipping and Ordering

Category	21346 - Contactors, Definite Purpose, 60 Amp
Discount Schedule	CP1B
GTIN	00785901080817
Package Quantity	1
Weight	1.64 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ
Country of Origin	MX

document.

Generated: 11/23/2009 15:30:47

