



List Price \$225.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Operating Torque/Force	4 Inch-Pounds
Basic Switch (Plug-In Unit)	Standard
Actuator	Lever Arm (ordered separately)
Actuation	CW and CCW
Turret Head	Rotary Head (for Type C Lever Arms)
Plug-In Receptacle	Standard
Actuator Action	Spring Return - Low Differential
Total Travel	90°
Differential Travel	2°
Pre-Travel	5°
Approvals	UL Listed - CSA Certified - CE Marked
Body Material	Zinc Alloy
Connection Type	0.5 Inch NPT Conduit Entrance (screw clamp terminals)
Contact Operation	Snap Action
Contact Rating	NEMA A600/Q600
Contact Material	Silver Alloy
Contact Configuration	1 NO/1 NC
Ampere Rating	10A
Contact Form	Form Z - SPDT-DB
Maximum Voltage Rating	600V
Pilot Light	None
Operating Temperature Range	-20°F to 185°F
Type of Duty	Heavy Duty
Type	C

Shipping and Ordering

Category	21499 - Limit Switches, Heavy Duty, Type C
Discount Schedule	CP1
GTIN	00785901500728
Package Quantity	10
Weight	1.23 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 06/13/2011 18:25:19

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.