



1054869-1 Product Details



1054869-1

[Active](#)

SMA/QMA RF Connectors



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Adapter
- Connector Type = SMA
- Adapter Type = Jack-Jack
- Body Style = Straight
- With Panel Attachment

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [OSM BULKHEAD FEEDTHROUGH JACK TO JACK ADAPTER](#) (PDF, English)

Catalog Pages/Data Sheets:

- [RF COAXIAL SOLUTIONS FOR COMMUNICATIONS](#) (PDF, English)
- [SMA Connectors](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Adapter
- [Connector Type](#) = SMA
- [Adapter Type](#) = Jack-Jack
- [Body Style](#) = Straight
- [Body Material](#) = Stainless Steel
- [Body Finish](#) = Passivated
- [Center Contact](#) = With
- Captivated Contacts = With
- Dielectric Material = TFE Fluorocarbon

Mechanical Attachment:

- [Panel Attachment](#) = With
- [Panel Attachment Method](#) = Bulkhead
- [Panel Attachment Style](#) = Rear Mount

Electrical Characteristics:

- Frequency = DC - 18 GHz

Body Related Features:

- [Length \(mm \[in\]\)](#) = 22.20 [0.874]

Contact Related Features:

- Center Contact Material = Beryllium Copper
- Center Contact Plating = Gold over Copper

Configuration Related Features:

- Captivation Method = Epoxy

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

- Brand = AMP