


70-781T-1 Socket/15 Amp Rating, 300 Volts



Printed Circuit Board Mounting



BOLD-FACED PART NUMBERS ARE NORMALLY STOCKED

Standard Part Number	Description
70-781T-1	5 Pin, Printed Circuit Terminals


General Specifications

Characteristics	Units	Value
Number of Terminals		5
Electrical Rating		
Nominal Voltage Rating	Volts	300
Nominal Current Rating	Amps	15
Dielectric Strength		
Output to Input Terminals	V rms	2500
Temperature		
Operating Range:	°C	- 40 to + 80
Storage Range:	°C	- 40 to + 105
Construction		
Internal Metal Tracks		Copper Alloy, Zinc Plated
Terminals		Copper Alloy, Zinc Plated
Miscellaneous		
Socket Mounting:		Printed Circuit
Connection Method		Solder
Flamability Rating	Class	94V-0
Body Color		Light Gray
Product Certification		UL, CSA
Conformance		CE, RoHS
Weight	grams	18

Optional Mating Accessories



781 Relay



16-781SC

Standard Part Number

Description

Catalog Location

781

Relay

Section 1 p.10-11

16-781SC

Metal Hold-Down Clip

Section 3 p.8-11

**16-781SC
Metal Hold-Down Clip**
See Section 3 p.10-11

