

Electrical UL/CSA

Electrical IEC

Electronics

Consumer/Aftermarket

OEM Transportation

Terminal Blocks

Systems/Services/Software

Cooper Bussmann

Homepage About Cooper Bussmann Contact Us Privacy Legal Cooper Bussmann® Brand Site Map



FNM-8

Time-Delay Supplementary Fuses, 13/32 x 1-1/2 Inches

Product Information					
Product Type:	Fuse				
Product Family:	Electrical Power				
Upgrade Product:	LP-CC-8				
Brand:	Cooper Bussmann				
Sub-brand:	Fusetron				

Recommended Products						
Rec. Fuse Block:	BM603 Series					
Rec. Inline Fuse Holder:	<u>HPS</u>					
Rec. Panel-mount Fuse Holder:	HEB Series					
Rec. Modular Fuse Holder:	OPM-NG-SM3					
Rec. Fuse Clips:	5960 Series					
Rec. Cover:	SAMI-7 Series					

Physical Properties Dimensions: $1.5 \text{in.(L)} \times 0.41 \text{in.(W)} \times 0 \text{in.}$ (H)


Certifications UL Listed CSA Certified

Electrical Properti	es
Maximum AC Voltage:	250
Amperage Rating:	8
AC Interrupting Ratings:	10000 at 125V200 at 250V
Time Delay:	Yes

Time-Delay Ferrule Fuse

FNM

13/32" x 1-1/2"



Catalog Symbol: FNM

TIME-DELAY 1/10 TO 30A

Interrupting Rating - SEE CHART BELOW

UL Listed: STD. 248-14, 0-10/250Vac; 12-15/125Vac

FILE #E19180, GUIDE #JDYX

CSA Certified: 1-10/250Vac; CLASS 1422-01, 12-15/125Vac; FILE 53787


250Vac IR		250Vac	IR		250Vac	IR		125Vac	
FNM-1/10		FNM-1-1	/8	FNM-4 FNM-4-1/2 FNM-5-6/10 100A @ FNM-6 250Vac FNM-6-1/4 10,000 FNM-7 @ FNM-8 125Vac FNM-9 FNM-10	FNM-4			FNM-12	10,000 @ 125Vac
FNM-1/8		FNM-1-1	/4		FNM-4-1	/2		FNM-15	
FNM-15/100		FNM-1-4	/10		FNM-5			_	
FNM-2/10	35A @ F 250Vac F 10,000 F @ F 125Vac F	FNM-1-1	/2		FNM-5-6	/10		_	
FNM-1/4		FNM-1-6	/10		FNM-6			32Vac	
FNM-3/10		FNM-1-8	/10			/4	200A @	FNM-20	
FNM-4/10		FNM-2			FNM-7		250Vac 10,000 @ 125Vac	FNM-25	
FNM-1/2		FNM-2-1	/4		FNM-8			FNM-30	
FNM-6/10		FNM-2-1	/2		FNM-9		123 VaC	-	
FNM-3/4		FNM-2-8	/10				_		
FNM-8/10		FNM-3			_			_	
FNM-1		FNM-3-2	/10		_			_	
_		FNM-3-1	-3-1/2 –			_			

If 250Vac is needed for 12-30A, use FNW series.

Carton Quantity and Weight

Ampere	Carton	Weight		
Ratings	Qty	Lbs.	Kg.	
0-30	10	.125	.057	

C€



· Fibre tube.

· For circuits with high inrush currents.

· Formerly designated 5AB.

• Fusetron® Dual-Element fuse.



Recommended fuseblocks/fuseholders for 13/32" x 1-1/2" fuses

See Data Sheets listed below

• Open fuseblocks - 1104, 2104

• Finger-safe fuseholders - 1109, 1102, 1103, 1151

• Panel-mount fuseholders - 2114, 2113, 2108, 2112, 2109, 2140

• In-line fuseholders - 2127, 2126