



Model #: PS-615-HG-OEM

Power Strip with Hospital-Grade Plug & Receptacles (TUV tested to UL)



Highlights

- Versatile power distribution strip designed to be installed on any mobile cart,
 IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- Two 15-amp resettable circuit breakers
- · Lifetime product warranty

Description

Tripp Lite's PS-615-HG-OEM Power Strip is designed to be installed on any mobile cart, IV pole, etc. It is TUV tested to UL 1363A to supply power to plug-connected components of a movable eqiupment assembly that is rack-, table- or pedestal-mounted. Features 6 output receptacles, 15-ft. AC power cord and two built-in resettable circuit breakers that control power to all outlets and protect against overloads. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Applications

• Mobile carts, IV poles and other UL 1363A usages.

Package Includes

- PS-615-HG-OEM
- User manual with warranty information

Features

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 6 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Rugged all-metal housing withstands years of use without breakage
- 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- Optional-use keyhole mounting tabs and flanges
- · Switchless design prevents accidental shutoff

Specifications

Overview For Use in Patient Areas SYSTEM OVERVIEW 120VAC OUTPUT Frequency compatibility 50 / 60 Hz Output vot amp capacity (emps) 15A Overload protection 2 x 15amp breaker (1 line, 1 neutral) Outled unantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation Single row of 6 INPUT Recommended Electrical Service 15A, 120V Service NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord length (m) 4.572 Input cord length (m) 4.572 Input cord gauge, type 14.59aus, S.UT UEDS ALARNS & SWITCHES Very College of the College of	OVERVIEW		
SYSTEM OVERVIEW Voltage compatibility 120VAC OUTPUT Frequency compatibility 50 / 60 Hz Output volt amp capacity (amps) 15A Overload protection 2 x 15amp breaker (1 line, 1 neutral) Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation Single row of 6 INPUT Recommended Electrical Services Input connection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft) 15 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (ftbs) 3.55 Unit Dimensions (HWDřin) 3.75 x 2.5 x 1.5 Shipping Dimensions (HWDřin) 15 x 6 x 3.55 Unit weight (ftbs) 2.25 Material of construction Metal Integrated keyhole mounting Keyhole mounting tabs and flanges enable mounting to a variety of surfaces table tabs CERTIFICATIONS Additional International Approvals TUV			
Voltage compatibility 120VAC OUTPUT Frequency compatibility 50 / 60 Hz Output volt amp capacity (amps) 15A Overload protection 2 x 15amp breaker (1 line, 1 neutral) Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet ordentation Single row of 6 INPUT Recommended Electrical Service 15A, 120V Input cornection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord gauge, type 14 gauge, SJT LEDS ALARINS & SWITCHES Switches No power switch PHYSICAL Shipping weight (fbs) 3.55 Unit Dimensions (HWD/In) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/In) 15 x 6 x 3.56 Unit weight (fbs) 2.25 Material of construction Metal Integrated keyhole mounting Keyhole mounting tabs and flanges enable mounting to a variety of surfaces LEDS ALARINS TUV tested to UL 1363A Approvals TUV tested to UL 1363A		For Use in Patient Areas	
CUTPUT Frequency compatibility 50 /60 Hz Output voit amp capacity (amps) 15A Output voit amp capacity (amps) 2 x 15amp breaker (1 line, 1 neutral) Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation Single row of 6 INPUT Recommended Electrical 15A, 120V Service 15A, 120V Service 15A, 15P-HG Hospital-Grade Input cornection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord gauge, type 14 gauge, SJT LEDS ALARINS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/lin) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/lin) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/lin) 14.65 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting the mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals MARRANTY Product Warranty Period I Inferime I Inferim			
Frequency compatibility 50 / 60 H2 Output voit amp capacity (amps) 15A Overload protection 2 x 15amp breaker (1 line, 1 neutral) Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation 5 single row of 6 INPUT Recommended Electrical 15A, 120V Input connection type NEMA 5-15R-HG Hospital-Grade Input cord length (ft.) 15 Input cord length (ft.) 15 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Witte weight (libs) 2.5 Material of construction Metal Integrated keyhole mounting Reyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs. Receptacle Color White CERTIFICATIONS Additional International Approvals Additional International Approvals Product Warranty Period I Lifetime		120VAC	
Output voit amp capacity (amps) Overload protection Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation Single row of 6 INPUT Recommended Electrical Services Input connection type NEMA 6-15P-HG Hospital-Grade Input cord length (ft.) If 5A, 120V Input cord length (ft.) Input cord length (ft.) Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (libs) 3.55 Unit Dimensions (HWD/lin) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/lin) Lite of a suffice of construction Metal Integrated keyhole mounting Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals Virtelines I titelines			
(amps) 2 x 15amp breaker (1 line, 1 neutral) Outlet quantity / type 6 x NEMA 5-15R-HG Hospital-Grade Outlet orientation Single row of 6 INPUT Recommended Electrical Services 15A, 120V Input connection type NEMA 6-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White Act line cord color White Additional International Approvals TUV tested to UL 1363A WARRANTY It refines	Frequency compatibility	50 / 60 Hz	
Outlet quantity / type		15A	
NPUT Recommended Electrical service	Overload protection	2 x 15amp breaker (1 line, 1 neutral)	
INPUT Recommended Electrical Service 15A, 120V Service 11Dut connection type NEMA 5-15P-HG Hospital-Grade 1 Input cord length (ft.) 15 Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch 15A, 120V PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15.76 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White CERTIFICATIONS Additional International Approvals Tuty tested to UL 1363A WARRANTY Product Warranty Period International International Product Warranty Period International Internationa	Outlet quantity / type	6 x NEMA 5-15R-HG Hospital-Grade	
Input connection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (libs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit unique (libs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Ac line cord color White Ac line cord color White CERTIFICATIONS Additional International TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime Integrated keynole mounting Lifetime	Outlet orientation	Single row of 6	
Service Input connection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 15 Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES No power switch PHYSICAL **** Shipping weight (ibs) 3.55 Unit Dimensions (HWD/In) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/In) 15 x 6 x 3.55 Unit weight (ibs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY **Iffetime*	INPUT		
Input cord length (ft.) Input cord length (m) 4.572 Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals Approvals WARRANTY Product Warranty Period Lifetime		15A, 120V	
Input cord length (m) Input cord gauge, type 14 gauge, SJT LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals Unit Versted to UL 1363A WARRANTY Product Warranty Period Lifetime	Input connection type	NEMA 5-15P-HG Hospital-Grade	
Input cord gauge, type LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime	Input cord length (ft.)	15	
LEDS ALARMS & SWITCHES Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime	Input cord length (m)	4.572	
Switches No power switch PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	Input cord gauge, type	14 gauge, SJT	
PHYSICAL Shipping weight (lbs) 3.55 Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces tabs Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	LEDS ALARMS & SWITCHES		
Shipping weight (lbs) Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime	Switches	No power switch	
Unit Dimensions (HWD/in) 13.75 x 2.5 x 1.5 Shipping Dimensions (HWD/in) 15 x 6 x 3.55 Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces about the cord color white AC line cord color CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	PHYSICAL		
Shipping Dimensions (HWD/in) Unit weight (lbs) 2.25 Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	Shipping weight (lbs)	3.55	
Unit weight (Ibs) 2.25 Material of construction Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White AC line cord color CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime	Unit Dimensions (HWD/in)	13.75 x 2.5 x 1.5	
Material of construction Metal Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime		15 x 6 x 3.55	
Integrated keyhole mounting tabs and flanges enable mounting to a variety of surfaces Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals TUV tested to UL 1363A WARRANTY Product Warranty Period Lifetime	Unit weight (lbs)	2.25	
Receptacle Color White AC line cord color White CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	Material of construction	Metal	
AC line cord color White CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime		Keyhole mounting tabs and flanges enable mounting to a variety of surfaces	
CERTIFICATIONS Additional International Approvals WARRANTY Product Warranty Period Lifetime	Receptacle Color	White	
Additional International Approvals WARRANTY Product Warranty Period Lifetime	AC line cord color	White	
Approvals WARRANTY Product Warranty Period Lifetime	CERTIFICATIONS		
Product Warranty Period Lifetime		TUV tested to UL 1363A	
Product Warranty Period (U.S., Canada & Puerto Rico)	WARRANTY		
	Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3719.

© 2010 Tripp Lite. All Rights Reserved.