


Cooper Bussmann Homepage About Cooper Bussmann Contact Us Privacy Legal Cooper Bussmann® Brand Site Map	FNQ Time-De	-25 elay Supplementary Fuse,	500V, 25A, 13/32 - 1-1/2	Inches	
	Product Informat				
	Product Type:	Fuse			
	Product Family:	Electrical Power			
	Brand:	Cooper Bussmann			
	Recommended Pi	roducts		rtifications	
	Rec. Fuse Block:	BM603 Series	CS	A Certified	
	Rec. Inline Fuse Holder:	HEB Series			
	Rec. Panel-mount Fuse Holder:	HPS Series	Electrical Prope Maximum AC	500	
	Rec. Modular Fuse	e <u>CHM Series</u>	Voltage:		
	Holder:		Amperage Rating		
	Rec. Fuse Clips:	5960 Series	AC Interrupting Ratings:	 10000 at 50 	VOV
	Rec. Cover:	SAMI-7 Series			
			Time Delay:	Yes	
	Physical Properties				
	Dimensions:	1.5in.(L) × 0.41in.(W) × (H)	0in.		

Bussmann®

FNQ

Tron[®] Time-Delay Fuses 13/32" x 1-1/2" Midget 500 Volt, 1/10-30 Amps





Catalog Symbol: FNQ (5AG) TIME-DELAY 1/10 TO 30A 500Vac (OR LESS) Interrupting Rating:10,000A UL LISTED, STD 248-14, (GUIDE # JDYX, FILE # E19180) CSA CERTIFIED (CLASS 1422-01; FILE 53787)

Catalog Symbol and Ampere Ratings


		-	
FNQ-1/10	FNQ-8/10	FNQ-3-2/10	FNQ-9
FNQ-1/8	FNQ-1	FNQ-3-1/2	FNQ-10
FNQ-15/100	FNQ-1-1/8	FNQ-4	FNQ-12
FNQ-3/16	FNQ-1-1/4	FNQ-4-1/2	FNQ-14
FNQ-2/10	FNQ-1-1/2	FNQ-5	FNQ-15
FNQ-1/4	FNQ-1-6/10	FNQ-5-6/10	FNQ-20
FNQ-3/10	FNQ-2	FNQ-6	FNQ-25
FNQ-4/10	FNQ-2-1/4	FNQ-6-1/4	FNQ-30
FNQ-1/2	FNQ-2-1/2	FNQ-7	_
FNQ-6/10	FNQ-3	FNQ-8	—

Carton Quantity and Weight							
Ampere	Carton	Weight*					
Ratings	Qty –	Lbs.	Kg.				
1-30	10	.180	.082				


* Weight per carton.

- Fibre tube.
- Nickel plated brass endcaps.
- For motor control transformers and other circuits with in-rush currents.

Time-Current Characteristic Curve-Average Melt



RMS SYMMETRICAL IN AMPERES



C€

