



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU750XL

SmartOnline Expandable Tower UPS System - On-line, double-conversion protection for mission-critical applications

Highlights



- 750VA/600W on-line expandable runtime tower UPS system
- HID-compliant USB port, serial port and SNMP/WEB card slot
- Maintains 120V +/-2% output during overvoltages to 138V and brownouts as low as 65V
- NEMA 5-15P (120V 15A) input plug, 6 x NEMA 5-15R outlets, two individually controllable single-outlet load banks
- Fault-tolerant auto-bypass
- \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Description

The SU750XL on-line, double-conversion UPS protects critical server, networking or telecommunications equipment from blackouts, brownouts, voltage fluctuations and surges. Large-capacity 750VA/600W UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at 120V AC (+/-2%). Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS systems. True sine wave output and zero transfer time offer guaranteed compatibility with all equipment types. Includes 6 UPS supported outlets; 2 single-outlet load banks can be independently controlled via a software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment. Extended runtime available with optional BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs. Includes slot for internal SNMP/WEB card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data. Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Includes Tripp Lite's PowerAlert UPS power management software. Compatible with Tripp Lite's Watchdog service monitoring/rebooting software. Upright tower form factor; attractive all-black color scheme.

Applications

- Ideal for protection of critical 120V servers, networking equipment and sensitive electronics. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.

Package Includes

- SU750XL UPS System
- PowerAlert Software CD and cabling
- EPO (Emergency Power Off) cabling
- Owner's manual with warranty information

Features

- True on-line, double-conversion UPS provides constant, pure sine wave AC output
- Maintains continuous operation with zero transfer time through blackouts, brownouts, voltage fluctuations and surges
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems

- Accepts input voltages between 80-138V (65-138V at loads under 70%), regulating output to 120V AC +/-2%
- 750VA/600W output capacity with 6 x NEMA5-15R outlets
- Two built-in individually switchable load banks can be controlled via software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment (1 outlet per bank)
- Standard internal battery set provides 11 min. runtime at half load and 4 min. at full load
- Extended runtime available with optional BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- DB9 serial network interface supports RS-232 and contact closure messaging
- Slot for optional SNMP/WEB card (part# SNMPWEBCARD)
- Included PowerAlert UPS power management software and cabling provides monitoring of in-depth site power conditions, full UPS status and fault warnings, output load level and load bank power control
- Compatible with Tripp Lite's WatchDog service monitoring/rebooting software (part# WATCHDOGSW)
- Fault-tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
- Diagnostic LEDs
- Upright tower format; attractive all-black color scheme
- \$250,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada only)
- 2-year warranty

Specifications

| SYSTEM OVERVIEW | |
|---|--|
| Voltage compatibility | 120V (110V, 100V) AC |
| Frequency compatibility | 50/60 Hz compatible |
| OUTPUT | |
| Output VA | 750 |
| Output watts | 600 |
| Output nominal voltage | 120 VAC |
| Output voltage regulation | Maintains full-time sine wave output within 2% of 120V, less than 5% total harmonic distortion |
| Output frequency regulation | Regulates line frequency to 50/60Hz +/- 0.05Hz |
| Outlet quantity / type | 6 x NEMA 5-15R |
| Customized load management receptacles | 2 individually controllable single-outlet load banks support load shedding and remote reboot on demand of locked network devices. Configurable with PowerAlert Software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices. |
| Overload protection | 15A input breaker |
| INPUT | |
| Maximum input amps | 6.2A |
| Input connection type | NEMA 5-15P |
| Input cord length | 10 ft. |
| Recommended Electrical Service | 15A 120V |
| BATTERY | |
| Full load runtime | 4 min. |
| Half load runtime | 11 min. |
| DC system voltage | 24VDC |
| Typical battery lifespan | 4-6 years typical |

| | |
|---------------------------------------|--|
| Battery recharge rate | 4-6 hours to 90% |
| Replacement Battery Cartridge | RBC24-SUTWR |
| VOLTAGE REGULATION | |
| Voltage regulation description | On-line, double-conversion power conditioning maintains output within 2% of 120V at all times |
| Overvoltage correction | Maintains output of 120V +/-2% during overvoltages to 138VAC |
| Brownout correction | Maintains output of 120V +/-2% during undervoltages to 80VAC |
| Severe brownout correction | Maintains output of 120V +/-2% during undervoltages to 65VAC (during load conditions of 70% or less) |
| LEDS ALARMS & SWITCHES | |
| Front panel LEDs | 14 status LEDs offer LINE POWER, ONLINE, BYPASS, ON BATTERY, OVERLOAD, BATTERY LOW, REPLACE BATTERY and FAULT status information. Also includes 4 LED meters for LOAD LEVEL/BATTERY LEVEL display (Battery level readout requires pressing power on/test switch) |
| Alarms | Multi-function audible alarm offers notification of UPS start, backup operation, low battery warning, overload, UPS fault and remote shutdown |
| Switches | Includes combination main power on/test and main power off switch |
| SURGE / NOISE SUPPRESSION | |
| AC suppression response time | Instantaneous |
| Dataline suppression | RJ45 1-line tel/DSL/Ethernet |
| EMI / RFI AC noise suppression | Yes |
| PHYSICAL | |
| Shipping weight (lbs) | 34.2 |
| Shipping weight (kg) | 15.4 |
| Shipping Dimensions (HWD/in) | 14.25 x 10 x 18.5 |
| Shipping Dimensions (HWD/cm) | 36.2 x 25.4 x 47 |
| Unit weight (lbs) | 28.7 |
| Unit weight (kg) | 12.92 |
| Unit Dimensions (HWD/in) | 10 x 6.75 x 13.25 |
| Unit Dimensions (HWD/cm) | 25.4 x 17.1 x 33.7 |
| Material of construction | Steel |
| Form factors supported | Tower |
| Cooling method | Fan |
| Battery Access | Supports battery access and hot-swap replacement without powering connected equipment off |
| ENVIRONMENTAL | |
| Relative Humidity | 0 to 95%, non-condensing |
| Storage Temperature | +5 to +122 degrees Fahrenheit/-15 to +50 degrees Celsius |

| | |
|--|---|
| Operating Temperature | +32 to +104 degrees Fahrenheit/0 to +40 degrees Celsius |
| Line mode BTU/hr. (Max.) | 305 BTU/hr. |
| COMMUNICATIONS | |
| Network monitoring port | Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. |
| Software and cabling included | PowerAlert Software CD-ROM and complete cabling |
| SNMP compatibility | Includes slot for optional SNMPWEBCARD accessory (#SNMPWEBCARD) |
| WatchDog compatibility | Compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of applications/OS or hard power off/on reboot of connected equipment ideal for unattended kiosk applications |
| LINE / BATTERY TRANSFER | |
| Transfer time from line power to battery mode | ZERO — on-line UPS continuously converts incoming AC to DC, then back to AC. When commercial power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power. |
| Low voltage transfer to battery power | Maintains continuous operation during undervoltages as low as 80V (65V during load conditions of 70% or less). Below the switchover point, output is supported from battery-derived AC power. |
| High voltage transfer to battery power | Maintains continuous operation without using battery power during overvoltages to 138V. Above this point, output is supported from battery-derived AC power. |
| SPECIAL FEATURES | |
| EPO port | Supports EPO (emergency power off) with included cabling |
| Cold Start | Inverter can be cold started to enable temporary AC output during a power failure |
| Appearance | Attractive all-black color scheme |
| BATTERY PACK ACCESSORY (optional) | |
| Battery Pack Accessory (optional) | BP24V15RT2U (limit 1), BP24V28-2U (limit 1), or BP24V70-3U (multi-pack compatible) |
| CERTIFICATIONS | |
| Certifications | Tested to UL1778 (USA), CSA C22.2 No. 107.3 (Canada), Class B (Emissions), RoHS-compliant, FCC Part 68/ Industry Canada (telecommunications) |
| WARRANTY | |
| Product Warranty Period | 2 years |
| Connected Equipment Coverage | \$250,000 (USA and Canada only) |
| Optional Coverage | 3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information. |

Related Items

| Extended Warranties | | |
|----------------------------|---|-----------------|
| WEXT3-500-1500 | 3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less | Qty: [optional] |
| WEXT5-500-1500 | 5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less | Qty: [optional] |

| External Battery Packs | | |
|-------------------------------|--|-----------------|
| BP24V28-2U | BP24V28-2U - External Battery Pack for UPS System | Qty: [optional] |
| BP24V70-3U | BP24V70-3U - External Battery Pack for UPS System | Qty: [optional] |
| BP24V15RT2U | BP24V15RT2U - External Battery Pack for UPS System | Qty: [optional] |

| Power Distribution | | |
|---------------------------|---|-----------------|
| PS7224 | Tripp Lite Power Strip - Multiple outlets wherever you need them | Qty: [optional] |
| PDU1215 | Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment | Qty: [optional] |

| Shutdown Cable Kits | | |
|----------------------------|---|-----------------|
| AS400CABLE KIT | Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers | Qty: [optional] |

| SNMP Accessories | | |
|-------------------------|--|-----------------|
| ENVIROSENSE | Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.) | Qty: [optional] |
| SNMPWEBCARD | For remote monitoring and control via SNMP, Web or telnet. | Qty: [optional] |

| Surge Protectors | | |
|-------------------------|--|-----------------|
| DTEL2 | Network Surge Suppressor - Essential protection for data and communication lines | Qty: [optional] |
| DNET1 | Network Surge Suppressor - Essential protection for data and communication lines | Qty: [optional] |
| DCATV | Network Surge Suppressor - Essential protection for TV/VCR coaxial lines | Qty: [optional] |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3299.

©2009 Tripp Lite. All Rights Reserved.