



List Price \$248.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

Technical Characteristics

Total Travel	0.25 Inches
Operating Torque/Force	3 Pounds
Basic Switch (Plug-In Unit)	Standard
Actuator	Top Roller-Plunger
Actuation	Horizontal
Turret Head	Top Plunger
Plug-In Receptacle	Standard
Actuator Action	Spring Return
Differential Travel	0.02 Inches
Pre-Travel	0.08 Inches
Approvals	UL Listed - CSA Certified - CE Marked
Body Material	Zinc Alloy
Contact Rating	NEMA A600/Q600
Contact Operation	Snap Action
Contact Material	Silver Alloy
Contact Configuration	1 NO/1 NC
Connection Type	0.5 Inch NPT Conduit Entrance (screw clamp terminals)
Ampere Rating	10A
Contact Form	Form Z - SPDT-DB
Maximum Voltage Rating	600V
Pilot Light	None
Type	C
Operating Temperature Range	0°F to 185°F
Type of Duty	Heavy Duty

Shipping and Ordering

Category	21499 - Limit Switches, Heavy Duty, Type C
Discount Schedule	CP1
GTIN	00785901500674
Package Quantity	1
Weight	1.08 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 06/13/2011 20:09:44

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.