■ MICROTORCH® MODELS MT–11 & MT–11K



Quick Jump:

A palm sized butane powered microtorch

- Compact palm size is perfect for tool kits and field service kits
- Produces an adjustable, wind resistant flame with temperatures up to 2500°F/1300°C, perfect for many microtorch applications
- Built-in Safety Lock with improved easy to use self-ignition system
- Meets Consumer Products Safety Commission (CPSC) Child Safety Requirements
- Powered by refillable "fuel cell" (included) with flame adjustment lever
- Built-in fuel level viewing window
- Use with Master Ultratane® Butane for best performance
- Pinpoint flame is perfect for soldering, desoldering, heat shrinking & terminating, heating, lighting and many other applications
- Patent Pending





ORDERING INFORMATION

MODEL NO.	ITEM NO.	DESCRIPTION
MT-11	10020	Microtorch, palm sized
MT-11K	10023	Microtorch, palm sized with Item No. 10448 ULTRATANE ® BUTANE

SPECIFICATIONS

Dimensions: 2.65"(L) x 1.05"(W) x 4.60"(H)

Recommended Fuel: Master

Ultratane® Butane

Approx. Run Time: 20 min. (full charge)

Shipping Weight: MT-11 - 1 lbs. /

MT-11K - 1 lbs.

Fuel Tank: "Refillable Fuel" Cell

Approx. Flame Temp: 2500° F/1300°C

(blue flame)

Net Weight: 2.9 oz./82 g



ULTRATANE ® BUTANE

Use Master Ultratane Butane for best performance. The only approved butane recommended to fuel all Master butane powered products.



Refillable Fuel Cell (Model # RC-31)

- Purest refining method possible
- Special non-clogging formula to permit extended use

Users should independently evaluate the suitability of the product for their application.

WARNING

The Department of Transportation Hazardous Material Regulations forbid carriage of butane or other flammable gas products on passenger aircraft. Do not pack this item or any other flammable gas item in any checked or carry-on baggage.

This product, when used for soldering and similar applications, produces chemicals known to the state of California to cause cancer and birth defects of other reproductive harm.

HOME BACK TO PRODUCT LISTING