



NORPS-12


9.53

Plastic Packaged CdS Photocell 104510 Rev 04

35.5







10

Description

The NORPS-12 is a CdS photoconductive cell with a spectral response similar to that of the human eye, encapsulated in a moisture-resistant coating and enclosed in a plastic casing.

Absolute Ratings Maximum

1.0 ftc. = 10.76 lux 1.0 lux = 0.093 ftc

Operating Temperature Storage Temperature Voltage (peak AC or DC) Power Dissipation at 30°C (1) -60 to +75°C -60 to +75°C 250 Volts 250mW

Electrical Characteristics (T_A=25°C, source at 2854°K)

Symbol	Parameter	Min.	Тур.	Max.	Units	Test Conditions
R_L	Light Resistance	5.4		12.6	kΩ	1 ftc. (2)
R_D	Dark Resistance	1.0			$M\Omega$	15 sec. after removal of test light.
λ_{P}	Spectral Peak		550		nm	

Specifications subject to change without notice

Notes: (1) Derate linearly to zero at 75°C.

(2) Cells light adapted at 30 to 50 Ftc for 16 hrs minimum prior to electrical tests.

5200 St. Patrick St., Montreal Que., H4E 4N9, Canada Tel: 514-768-8000 Fax: 514-768-8889

QF-84 Rev 3