

Model #: PS-415-HG-OEM

Power Strip with Hospital-Grade Plug & Receptacles (Approved for Use on Mobile Carts, Instruments and Diagnostic Equipment)



Highlights

- Versatile power distribution strip designed to be installed on any mobile cart,
 IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- Two 15-amp resettable circuit breakers
- · Lifetime product warranty

Description

Tripp Lite's PS-415-HG-OEM Power Strip is designed to be installed on any mobile cart, diagnostic equipment, instrument, IV pole, etc. It is TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted. Features 4 output receptacles, 15-ft. AC power cord and two built-in resettable circuit breakers that control power to all outlets and protect against overloads. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Applications

• Mobile carts, IV poles and other UL 1363A certified usages.

Package Includes

- PS-415-HG-OEM Power Strip
- Owner's manual and warranty information

Features

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Rugged all-metal housing withstands years of use without breakage
- 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff

Specifications

OVERVIEW	
Model Type	For Use in Patient Areas
SYSTEM OVERVIEW	
Voltage compatibility	120VAC
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output volt amp capacity (amps)	15A
Overload protection	2 x 15amp breakers (1 line, 1 neutral)
Outlet quantity / type	4 x NEMA 5-15R-HG Hospital-Grade
Outlet orientation	Single row of 4
INPUT	
Recommended Electrical Service	15A, 120V
Input connection type	NEMA 5-15P-HG Hospital-Grade
Input cord length (ft.)	15
Input cord length (m)	4.572
Input cord gauge, type	14 gauge, SJT
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping weight (lbs)	3.55
Unit Dimensions (HWD/in)	13.75 x 2.5 x 1.5
Shipping Dimensions (HWD/in)	15 x 6 x 3.55
Unit weight (lbs)	2.25
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White
AC line cord color	White
CERTIFICATIONS	
Approvals	TUV tested to UL 1363A
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3720.

© 2010 Tripp Lite. All Rights Reserved.